



Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546

ph 1-510-582-5031 - 1-800-510-7223

Avon Radial Ply

W.T.		Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Formula One Radial P{Ply								
18	245/640R13 (13247 A11) (13248W)	430	Call	11-12.5	11.75	20	25.20	12.6	9.50
20	270/660R13 (12242 A11)	569	Call	11-12.5	11.75	20	25.75	13.4	11.1
21	315/660R13 (11505 A11) (9847W)	561	Call	13-15	13.75	20	25.75	15.0	12.3
23	370/660R13 (9845 A11) (6021W)	597	Call	14-16	15.0	20	25.75	17.0	15.0

Avon Radial Ply

W.T.		Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	F3000 Radial Ply								
17	240/600R13 (13919 A11) 10952W)	438	Call	11-13	12.0	20	23.80	12.4	9.5
22	330/620R13 (9482 A11) (6021W)	557	Call	14-16	15.0	20	24.45	15.9	13.5

Avon Radial Ply

W.T.		Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	INDY Car Radials								
18	275/635R15 (13797 A11) (15675 A222)	530	Call	11-13	10.0	20	25.30	11.9	9.5
22	350/72015 (12700 A11) (16867 A222)	628	Call	14-16	14.0	20	28.31	16.3	13.5

Avon Radial Ply

W.T.		Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Formula Atlantic - INDY Lights								
15	340/600R13 (14188 A53) (16146 A333)	455	Call	10-12	10.0	20	23.70	11.0	9.4
21	330/60R15 (14189 A53) (16147 A333)	531	Call	14-16	14.0	20	24.40	15.5	13.3

Avon Radial Ply

W.T.		Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Group C, IMSA								
	300/650R17 (15586 A24)	535	Call	11-12.5	12.0	20	25.70	13.0	12.0
	300/650R18 (15205 A11) (15407 A24) (A545)	535	Call	11-12.5	12.0	20	25.70	13.0	12.0
	335645R18 (14744 A11) (15984 A545)	545	Call	13-14	13.0	20	25.55	14.2	13.1
	365/720R18 (15360) (5610 A545)	565	Call	14.5-16	14.5	20	28.39	15.9	14.4

Avon Bias Ply

W.T.		Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Formula B. F2, Early Sports Racers									
15	9.1/21.0-13 (6428 A11)	309	374	384	8.5-10.5	10.0	20	21	10.9	9.1
19	12.0/23.0-13 (7239 A11)	384	469	479	12-14	13.0	20	23.2	14.5	12.3

Avon Bias Ply

W.T.		Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Formula Atlantic - 2 liter Sports Racers									
9.3	9.0/20.0-13 (7210 A11) (15757 222)	289	354	364	8-10.5	10.0	20	20	10.6	9.2
20	13.0/23.0-13 7262 A11) (15760 222)	395	480	490	13-15	14.0	20	23.35	15.2	13.00

Avon Bias Ply

W.T.		Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Sports Racers - Spec Applications									
12	7.0/21.0-13 (11452 A11)	273	328	338	6-8	8.0	20	20.6	9.0	7.2
17	9.2/22.0-13 (11453 A11)	320	385	395	8.5-10.5	10.0	20	22.4	11.1	9.1
9.3	7.0/20.0-13 Call for Compounds A11-222-007	257	312	322	6-8	6.0	20	20.4	7.6	7.4
11.3	8.2/22.0-13 Call For Compounds A11-222-007	302	367	377	8-10	8.0	20	22.0	9.7	8.6

Avon Bias Ply

W.T.		Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	Formula B- Historic & Monoposto									
15	8.2/22.0-13 (3146 A11)	306	371	381	7-10	9.0	20	22.0	10.1	8.6
19	10.5/23.0-13 (4125 A11) Rear	384	459	469	9-11.5	11.0	20	23.5	12.3	10.3
15	9.1/21.0-13 (6428 A11)	309	374	384	8.5-10.5	10.0	20	21.0	10.9	9.1
19	12.0/23.0-13 (7239 A11)	384	469	479	12-14	13.0	20	23.2	14.5	12.3
20	13.0/23.0-13 7262 A11) (15760 222)	395	480	490	13-15	14.0	20	23.35	15.2	13.00
20	13.0/24.5-13 (6429 A11)	418	503	513	13-15	14.0	20	24.3	15.5	12.5

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,333,A11,007,222,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546

ph 1-510-582-5031 - 1-800-510-7223

Avon Bias Ply

W.T.	Formula 1 & Other	Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.5/16.0-10 (7340 A11) (10338 A15)	348	Call	8-9.5	9.0	20	15.9	9.3	8
	8.2/20.0-13 (2260 A11)(2555W)	271	Call	7-9	9.0	20	19.95	9.8	8.5
14	9.0/20.0-13 (7210 A11) (2553W)	289	Call	8-10.5	10.0	20	20.0	10.6	9.2
13	10.0/20.0-13 (2545 A11) (4134W)	308	Call	9-11	10.0	20	19.8	11.1	10.2
	10.0/20.0-13 (14763 A11 Kevlar)	308	Call	9-11	10.0	20	19.8	11.1	10.2
	10.0/21.0-13 (16577 A11) F1	335	Call	9-11	10.0	20	21.0	11.1	10.2
15	10.0/22.0-13 (9772 A15)	416	Call	9-12	11.0	20	22.1	11.9	10.3
15	10.0/22.0-13 (10358 A11)	336	Call	9-12	11.0	20	11.0	22.1	10.3
15	9.0/21.0-13 (4619 A15)	367	Call	8-10.5	10.0	20	21.0	10.9	9.1
15	9.0/21.0-13 (6428 A11)	309	Call	8-10.5	10.0	20	21.0	10.9	9.1
19	10.5/23.0-13 (2126 A11 Frt) (4125 A11 Rear)	384	Call	9-11.5	11.0	20	23.5	12.3	10.3
21	13.0/24.5-13 (6429 A11)	418	Call	13-15	14.0	20	24.3	15.5	12.5
27	15.0/26.0-13 (2133 A15) (2594 A15)	513	Call	15-18	16.0	20	25.75	17.8	15
28	16.2/26.0-13 (3354 A11) (5347W)	546	Call	16-18	17.0	20	25.8	18.8	16.3

Avon Bias Ply

W.T.	FIA - Can Am - USRRC - Other	Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.0/21.5-15 (14765 A11) (6881 A24) (123989 A56)	359	424	434	6.5-8.5	7.5	30	21.8	8.8	7.8
	8.7/21.5-15 (14754 A11) (6460 A24) (4871 A15)	393	458	468	7.5-9.5	8.0	30	22.1	9.7	8.4
	9.5/21.5-15 (4700 A24)	359	434	444	10.0	10.0	30	21.85	10.7	9.5
	9.5/21.5-15 (2829 A11) (3640 A15)	405	480	490	8-10	10.0	30	21.85	10.7	9.5
	10.7/21.5-15 (2036 A11) (2412 A15)	374	449	459	9-11	10.0	30	21.85	11.3	10.6
	10.7/21.5-15 (12417 A53) Kevlar	420	495	505	9-11	10.0	30	21.85	11.3	10.6
18	7.5/23.0-15 (5893 A24)	348	413	423	7-8.5	8.0	30	22.85	8.5	7.4
19	8.5/21.5-15 (6524 A24)	383	448	458	7-9.5	8.5	30	23.6	9.6	8.3
20	9.1/23.5-15 (6132 A11) (5978 A24)	409	474	484	8-9.5	8.5	30	23.55	9.9	9.1
18	10.5/23.0-15 (3101 A11)	424	499	509	9-12	11.0	30	23.55	12.0	10.3
18	10.5/23.0-15 4301 A24)	458	533	543	9-12	11.0	30	23.55	12.0	10.3
21	11.0/23.5-15 (3100 A11)	423	498	508	10-12	11.0	30	23.3	12.1	11.3
21	11.0/23.5-15 (4263 A24)	467	542	552	10-12	11.0	30	23.3	12.1	11.3
21	12.5/23.5-15 (2351 A11) (3733 A24)	483	568	578	11-13.5	12.0	30	23.3	13.3	12.7
21	9.5/25.0-15 (9928 A24) (14426 A11)	423	498	508	9-11	10.0	30	24.8	11.7	9.3
22	11.0/25.0-15 (4284 A24) (14427 A11)	453	528	538	10-12	12.0	30	24.7	13.6	11.3
24	13.0/25.0-15 (4319 A11)	471	556	566	11.5-14	14.0	30	24.8	15.4	13.2
24	13.0/25.0-15 (3731 A24)	521	606	616	11.5-14	14.0	30	24.8	15.4	13.2
27	15.0/26.0-15 (3127 A11) (4302 A24)	529	634	644	14-17	16.0	30	25.8	17.4	15
27	16.2/26.0-15 (3831 A11)	562	667	677	16-19	16.0	30	25.8	17.9	16.3
25	12.5/27.0-15 (4285 A24) (11764 A11)	476	561	571	11.5-14.5	13.0	30	27.0	15.3	12.5
27	14.0/27.0-15 (3358 A11) (4300 A24)	482	587	597	13-16	15.0	30	27.1	16.7	14
28	16.0/27.0-15 (3099 A11)	544	649	659	15-19	16.0	30	27.5	16.8	16.1
17	9.5/23.5-16 (3533 A24)	394	459	469	8.5-10.5	8.5	30	23.6	9.8	9.5
19	10.0/23.0-16 (11760 A11) (3742 A24)	423	498	508	10-12	10.0	30	23.6	11.1	10.3
18	11.0/23.5-16 (3131 A11)	441	516	526	10-12	11.0	30	23.6	12.6	11.3
18	11.23.5-16 (4172 A24)	470	545	555	10-12	11.0	30	23.6	12.6	11.3
18	11.0/23.5-19 (15111 A37)	441	516	526	10-12	11.0	30	23.6	12.6	11.3
22	11.0/25.0-126 (2992 A11) (5260 A37)	472	547	557	10-12	12.0	30	24.75	13.3	11.3
22	12.5/23.5-16 (3069 A11) (3831 A24 (3604 A15)	499	594	604	11-13.5	12.0	30	23.4	13.6	12.7
23	12.5/25.0-16 (4247 A11)	513	598	608	11.5-14	13.0	30	24.8	14.2	12.5
23	12.5/25.0-16 (4147 A24)	513	598	608	11.5-14	13.0	30	24.8	14.2	12.5
24	13.5/25.0-16 (11759 A11)	471	576	586	12-14.5	14.0	30	25.0	15.2	13.4
24	13.5/25.0-16 (3845 A24)	532	637	647	12-14.5	14.0	30	25.0	15.2	13.4
26	14.0/27.0-16 (2993 A11)	483	588	598	13-16	15.0	30	27.1	16.7	14.0
26	14.0/27.0-16 (15020 A24)	542	647	657	13-16	15.0	30	27.1	16.7	14.0

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,333,A11,007,222,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546

ph 1-510-582-5031 - 1-800-510-7223

Avon Radial Ply F.C., F1000, S2.

Formula Continental, S2 & F1000/FB Tires

	Slick			Rim	Rim	AT			
		Sizes	Used	PSI	Diam	Sec	T.W.		
175/530R13 (17614 222) FOR 2021	280	6-8	6.0	20	20.95	7.75	7.0		
200/5656R13 (17615 222) FOR 2021	309	8-10	8.0	20	22.32	10.2	9.2		

Avon Bias Ply - SCCA

Formula Continental, S2 & F1000/FB Tires

	Slick	Hist New	Hist Old	Rim	Rim	AT			
		Sizes	Used	PSI	Diam	Sec	T.W.		
9.3 7.0/20.0-13 (15502 007) (15763 222)	257	312	322	6-8	6.0	20	20.8	7.6	7.4
11.3 8.2/20.0-13 (16479 007) (15766 222)	302	367	377	8-10	8.0	20	22.0	9.7	8.6

Formula Continental, S2 & F1000/FB WETS

		Sizes	Used	PSI	Diam	Sec	T.W.	
160/530R13 (13593 W561)	266	Molded Wets	5.5-7.5	6.0	20	20.9	7.4	6.3
180/565R13 (13594 W561)	318	Molded Wets	5.5-8.5	7.0	20	22.1	8.7	7.2

SCCA Stohr, P1, P2, S.V and F.M.

		Sizes	Used	PSI	Diam	Sec	T.W.
10 8.2/20.0-13 (16881 222)	283	7-9	9.0	20	19.95	9.8	8.5
14 10.0/22.0-13 (16647 222)	340	9-12	11.0	20	22.1	11.9	10.3

F.A & 2 liter Sports Racers

		Wets	Sizes	Used	PSI	Diam	Sec	T.W.
14 9.0/20.0-13 (7210 A11) (15757 222)	294	Call	8-10	9.0	20	20.0	10.6	9.2
20 13.0/23.0-13 (7262 A11) (15760 222)	399	Call	13-15	14.0	20	23.25	15.2	13.0

SCCA GT3, E Production

		Wets	Sizes	Used	PSI	Diam	Sec	T.W.
17.5 9.0/23.3-15 (16972 A545)	328	Call	7.0-9.5	7.0	30	23.47	9.5	9

Avon Radial Ply F.A. Sports Racers

Norma, Wolf, DP02. Indy Lights

Formula Atlantic 15" Radials

		Wets	Rim	Rim	AT				
		Sizes	Used	PSI	Diam	Sec	T.W.		
15 240/600R15 (14188 A53) (16146 333)	455	Call	10-12	10.0	20	23.7	11.0	9.4	
21 330/620R15 (14189 A53) (16147 333)	531	Call	14-16	14.0	20	24.4	15.5	13.3	

Special Application Radials

		Wets	Sizes	Used	PSI	Diam	Sec	T.W.
11.9 175/530R13 Spec Order	Call	Call	6.5-7.5	7.0	20	20.9	8.0	7.1
12 180/550R13 Special Order	Call	Call	8.5-9.5	9.0	20	21.8	9.5	7.3
13.2 195/530R13 Special Order	Call	Call	8-9	8.5	20	20.8	9.7	8.1
14 210/550R13 (15485 007) (16287 333)	356	Call	9-10	10.0	20	21.8	10.6	8.3
14 210/550R13 (14734 W561) WET	395		9-10	10.0	20	21.8	10.6	8.3
15.6 230/550R13 (15505 007) (16069 222) (16988 333)	404	Call	9-11	10.0	20	21.8	11.4	9.2
17.7 250/570R13 (15616 007) (7941 333)	413	Call	9-11	10.0	20	22.6	11.4	9.7
17.7 250/570R13 (15261 W534)	444		9-11	10.0	20	22.6	11.4	9.7
16.6 290/570R13 (15714 007) (16288 333)	444	Call	10.5-12.5	11.75	20	22.8	12.5	11.1
18.4 300/600R13 (15506 007) (16070 222) (16989 333)	490	Call	13-14	13.0	20	23.9	14.7	11.9

W.T. Formula Atlantic - INDY Lights

	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
15 240/600R15 (14188 A53) (16146 A333)	455	Call	10-12	10.0	20	23.70	11.0	9.4
21 330/620R15 (14189 A53) (16147 A333)	531	Call	14-16	14.0	20	24.40	15.5	13.3

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,333,A11,007,222,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546

ph 1-510-582-5031 - 1-800-510-7223

Road Race - Avon Bias Ply

Autocrossing Compounds - Not Super Soft	Slick	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
8.5/16.0-13 (7340 A11)	348	8-9.5	9.0	20	15.9	9.3	8.0
7.0/20.0-13 (10992 A11)	257	6-8	6.0	20	20.8	7.6	7.4
7.0/21.0-13 (11452 A11)	273	6-8	8.0	20	20.6	9	7.2
8.2/20.0-13 (2260 A11)	271	7-9	9.0	20	19.95	9.8	8.5
9.0/20.0-13 (7210 A11)	289	8-10.5	10	20	20.0	10.6	9.2
10.0/20.0-13 (2545 A11)	308	9-11	10	20	19.8	11.1	10.2
10.0/20.0-13 (14763 A11) Kevlar	308	9-11	10	20	19.8	11.1	10.2
9.0/21.0-13 (6428 A11)	309	8-10.5	10.0	20	10.9	9.1	9.1
10.0/21.0-13 (16577 A11) F1	335	9-11	10	20	21.0	11.1	102
8.2/22-13 (3146 A11)	306	7-9	9.0	20	22.0	10.1	8.6
9.2/22.0-13 (11453 A11)	320	8.5-10.5	10.0	20	22.4	11.1	9.1
10.0/22.0-13 (10358 A11)	336	9-12	11.0	20	22.1	11.9	10.3
10.5/23.0-13 (2126 A11) F1 Front	384	9-11.5	11.0	20	23.5	12.3	10.3
10.5/23.0-13 (4125 A111) Rrear Use	384	9-11.5	11.0	20	23.5	12.3	10.3
12.0/23.0-13 (7239 A11)	384	12-14	13.0	20	23.2	14.5	12.3
13.0/823.0-13 (7262 A11)	395	13-15	14.0	20	23.25	15.2	13.0
13.0/24.5-13 (6429 A11)	418	13-15	14.0	20	24.3	15.5	12.5
15.0/26.0-15 (2133 A11)	513	15-18	16.0	20	25.75	17.8	15
16.2/26.0-13 (3354 A11)	546	16-18	17.0	20	25.8	18.8	16.3
8.0/21.5-15 (14765 A11) (6881 A24)	345	6.5-8.5	7.5	30	21.8	8.8	7.8
8.7/21.5-15 (14754 A11) (6460 A24)	383	7.5-9.5	8.0	30	22.1	9.7	8.4
9.5/21.5-15 (4700 A24)	359	8-10	10.0	30	21.85	10.7	9.5
9.5/21.5-15 (2829 A11) (3640 A15)	424	8-10	10.0	30	10.7	9.5	9.5
10.7/21.5-15 (2036 A11) (2412 A15)	383	9-11	10.0	30	21.85	11.3	10.6
10.7/21.5-15 (12417 A53) Kevlar	420	9-11	10.0	30	21.85	11.3	10.6
7.5/23.5-15 (5983 A24)	348	7-8.5	8.0	30	22.8	8.5	7.4
8.5/23.5-15 (6524 A11)	383	7-9.5	8.5	30	23.6	9.6	8.3
9.1/23.5-15 (6132 A11) (5978 A24)	409	8-9.5	8.5	30	23.55	9.9	9.1
10.5/23.0-15 (3101 A11)	424	9-12	11.0	30	23.55	12.0	10.3
10.5/23.0-15 (4301 A11)	458	9-12	11.0	30	23.55	12.0	10.3
11.0/23.5-15 (3100 A11)	423	10-12	11.0	30	23.3	12.1	11.3
11.0/23.5-15 (4263 A24)	467	10-12	11.0	30	23.3	12.1	11.3
12.5/23.5-15 (2351 A11)	483	11-13.5	10.0	30	23.3	13.3	12.7
9.5/25.0-15 (9928 A24) (14426 (A11)	423	9-11	10.0	30	24.8	11.7	9.3
11.0/25.0-15 (4284 A24) (14427 A11)	453	10-12	12.0	30	24.7	13.6	11.3
13.0/25.0-15 (4319 A15)	471	11.5-14	14.0	30	24.8	15.4	13.2
13.0/25.0-15 (3731 A24)	521	11.5-14	14.0	30	24.8	15.4	13.2
15.0/26.0-15 (3127 A11) (4302 A24)	529	14-17	16.0	30	25.8	17.4	15
16.2/26.0-15 (3831 A11)	562	16-19	16.0	30	25.8	17.9	16.3
12.5/27.0-15 4285 A24) (11764 A11)	476	11.5-14.5	13.0	30	27	15.3	12.5
14.0/27.0-15 (3358 A11) (4300 A24)	482	13-16	15.0	30	27.1	16.7	14.0
16.0/27.0-15 (3099 A11)	544	15-19	16.0	30	27.5	16.8	16.1
10.0/23.5-16 (11760 A11) (3742 A24)	423	10-12	10.0	30	23.6	11.1	10.3
11.0/23.5-16 (3131 A11)	441	10-12	11.0	30	23.6	12.6	11.3
11.0/23.5-16 (4172 A24)	470	10-12	11.0	30	23.6	12.6	11.3
11.0/25.0-16 (2992 A11) (5260 A37)	472	10-12	11.0	30	23.6	12.6	11.3
12.5/25.0-16 (4247 A11)	513	10-12	11.0	30	23.6	12.6	11.3
12.5/25.0-15 (4147 A24)	513	10-12	11.0	30	23.6	12.6	11.3
12.5/27.0-16 (15006 A24)	545	11.5-14	13.0	30	27.0	15.3	12.5
13.5/25.0-16 (11759 A11)	471	12-14.5	14.0	30	25.0	15.2	13.4
13.5/25.0-165 (3845 A24)	532	12-14.5	14.0	30	25.0	15.2	13.4
14.0/27.0-15 (2993 A11)	483	13-16	15.0	30	27.1	16.7	14.0
14.0/27.0-16 15020 A24)	542	13-16	15.0	30	27.1	16.7	14.0

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,333,A11,007,222,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



Note: The A15 is a Hill Climb, Autocrossing and a Wet use tire. For wet use we hand grove these tires in house. These tires have more tread depth compared to other slicks.

Avon Bias Ply
Vary Soft to Super Soft Tires

Avon Bias Ply - Road Race, Auto X, H.C & Wet.
Autocrossing - Soft to Supersoft Tires

These Tires can be Hand Cut into wets

				Rim	Rim	AT			
	Slick	INT.	WET	Sizes	Used	PSI	Diam	Sec	T.W.
10-13"									
7.0/16.0-10 (13758 A15)	280	Call	Call	6.5-8	7.5	20	15.9	7.8	7.0
8.5/16.0-10 (10338 A11)	364	Call	Call	8-10.5	9	20	15.9	9.3	8.0
8.2/20.0-13 (2555 A15)	271	Call	Call	7-9	9	20	20.0	9.8	8.5
8.2/22.0-13 (14209 A15)	385	Call	Call	9-Jul	9	20	22.0	10.1	8.6
9.0/20.0-13 (2553 A15)	289	Call	Call	8-10.5	10	20	20.0	10.6	9.2
9.0/21.0-13 (4619 A15)	367	Call	Call	8-10.5	10	20	10.9	9.1	9.1
10.0/20.0-13 (4134 A15)	308	Call	Call	11-Sep	10	20	19.8	11.1	10.2
10.0/22.0-13 (9772 A15)	419	Call	Call	12-Sep	11	20	22.1	11.9	10.3
10.5/23.0-13 (2594 A15 Rec Front)	363	Call	Call	9-11.5	11	20	23.5	12.3	10.3
10.5/23.0-13 (4864 A15 Rec Rear)	458	Call	Call	9-11.5	11	20	23.5	12.3	10.3
12.0/23.0-13 (2888 A15)	473	Call	Call	14-Dec	10	20	23.2	14.5	12.3
13.0/23.0-13 (2391 A15)	487	Call	Call	13-15	14	20	23.3	15.2	13.0
15.0/26.0-13 (2595 A15)	511	Call	Call	15-18	16	20	25.8	17.8	15.0
16.2/26.0-13 (5347 A15)	596	Call	Call	16-18	17	20	25.8	18.8	16.3
15"									
8.0/21.5-15 (4867 A15 6 Ply)	376	Call	Call	6.5-8.5	7.5	30	21.8	8.8	7.8
8.7/21.5-15 (4871 A15)	409	Call	Call	7.5-9.5	8	30	22.1	9.7	8.4
9.5/21.5-15 (3640 A15)	405	Call	Call	10-Aug	10	30	21.9	10.7	9.5
10.0/21.5-15(3503 A15)	431	Call	Call	8.5-11	10	30	21.9	11	10.0
10.7/21.5-15 (2412 A15)	374	Call	Call	9.11	10	30	21.9	11.3	10.6
8.5/23.5-15 (9318 A15)	394	Call	Call	7.5-9.5	8.5	30	23.6	9.6	8.5
9.1/23.5-15 (5602 A15)	421	Call	Call	8-9.5	8.5	30	23.6	9.9	8.8
10.5/23.0-15 (3283 A15)	431	Call	Call	12-Sep	11	30	23.55	12	10.3
11.0/23.5-15 (3284 A15)	431	Call	Call	12-Oct	11	30	23.0	12.1	11.3
11.0/25.0-15 (2459 A15)	448	Call	Call	12-Oct	12	30	24.7	13.6	11.3
13.0/25.0-15 (2424 A15)	553	Call	Call	11.5-14	14	30	24.8	15.4	13.2
15.0/26.0-15 (3286 A15)	520	Call	Call	14-17	16	30	25.8	17.4	15.0
12.5/27.0-15 (2253 A15)	547	Call	Call	13-16	15	30	27.1	15.2	12.5
16.0/27.0-15 (3593 A15)	622	Call	Call	15-19	16	30	27.5	16.8	16.1
16"									
8.5/23.3-16 (9806 A15)	414	Call	Call	7.5-8	8	30	23.6	9.6	8.8
9.5/21.5-16 (3647 A15)	436	Call	Call	8.5-10.5	8.5	30	23.6	9.8	9.5
10.0/23.5-16 (3106 A15)	420	Call	Call	9-11	10	30	23.6	11.1	10.0
11.0/23.5-16 (2458 A15)	453	Call	Call	10-12	12	30	23.5	12.6	11.3
11.0/25.0-16 (2994 A15)	472	Call	Call	10-12	12	30	24.8	13.3	11.3
12.5/23.5-16 (3604 A15)	499	Call	Call	11.5-13.5	13.75	30	23.4	13.8	12.7
12.5/25.0-16 (12866 A15)	528	Call	Call	11.5-13.5	13	30	24.8	14.2	12.5
13.5/25.0-16 (4116 A15)	482	Call	Call	12-14.5	14	30	25	15.2	13.4
14.0/27.0-16 (2995 A15)	496	Call	Call	13-16	14	30	27.2	15.8	14.0

Avon Bias Ply - Auto X, H.C & Wet

Auto X, H.C., A92 Comp. - Super Soft

	Slick	INT.	WET	Rim	Rim	AT			
	Slick	INT.	WET	Sizes	Used	PSI	Diam	Sec	T.W.
7.2/20.0-13 (14254 A92)	309	Call	Call	6-8	8.0	20	20.2	9	7.1
8.2/20.0-13 (14140 A92)	321	Call	Call	7-9	9.0	20	20.0	9.75	8.5
9.0/20.0-13 (14143 A92)	349	Call	Call	8-10	10.0	20	20.0	10.65	9.2
10.0/20.0-13 (14251 A92)	349	Call	Call	9-11	10.0	20	19.8	11.1	10.2
7.0/21.0-13 (14207 A92)	315	Call	Call	6-8	8.0	20	20.6	9	7.2
8.5/21.5-13 (14176 A92)	353	Call	Call	7.5-9	9.0	20	20.8	10.2	8.5
9.0/21.0-13 (14177 A92)	360	Call	Call	8-10	10.0	20	21.0	10.9	9.1
9.2/22.0-13 (14142 A92)	399	Call	Call	8.5-10.5	10.0	20	22.4	11.1	9.1

Hard **Avon Compounds** **Medium** **Very Soft** **Super Soft**

A29,A64,A84,A37,A745,A514,A24,A545,333,A11,007,222,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!