



Roger Kraus Racing

Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone 510-582-5031 Order Line 800-510-7223

Avon ACB-10 January 2020



ACB-10 Front



ACB-10 Rear

Avon ACB-10

WT	ACB 10 Sport			K.G.	Compound	Price	RIM SIZES	AT	PSI	DIA	SEC	T.W.
11.15	6.0/21.0-13 M	185/50-13	76V	4.85	12157 A-60	230	5.5 TO 6.5	20	20.8	7.3	5.9	
11.16	6.0/21.0-13 M	185/50-13	77V	5.06	6363 A-30	230	5.5 TO 6.5	20	20.8	7.3	5.9	
11.15	6.0/21.0-13 M	185/50-13	77V	4.85	6356 A-24	230	5.5 TO 6.5	20	20.8	7.3	5.9	
12.48	7.0/21.0-13 M	195/50-13	78V	5.66	12452 A-60	259	6.0 TO 7.5	20	20.7	7.6	6.9	
12.48	7.0/21.0-13 M	195/50-13	78V	5.66	6898 A-30	259	6.0 TO 7.5	20	20.7	7.6	6.9	
12.48	7.0/21.0-13 M	195/50-13	85V	5.66	6894 A-24	259	6.0 TO 7.5	20	20.7	7.6	6.9	
12.90	7.0/22.0-13 M	215/50-13	85V	5.85	6357 A-31	268	5.5 TO 7.5	20	21.9	8	7.1	
13.21	7.0/22.0-13 M	215/50-13	85V	5.99	6364 A-24	268	5.5 TO 7.5	20	21.9	8	7.1	
13.67	8.0/22.0-13 M	245/45-13	89V	6.2	6899 A-31	278	7.0 TO 8.5	20	22.1	8.7	8.1	
13.67	8.0/22.0-13 M	245/45-13	78V	6.2	12514 A-60	278	7.0 TO 8.5	20	22.1	8.7	8.1	
13.67	8.0/22.0-13 M	245/45-13	89V	6.2	6895 A-24	278	7.0 TO 8.5	20	22.1	8.7	8.1	
13.43	7.0/22.0-15 M	195/45-15	78V	6.09	6509 A-31	290	6.5 TO 7.5	20	21.7	7.8	7.1	
13.43	7.0/22.0-15 M	195/45-15	78V	6.09	12144 A-60	290	6.5 TO 7.5	20	21.7	7.8	7.1	
13.91	8.0/22.0-15 M	215/40-15	80V	6.31	6587 A-31	303	7.0 TO 8.5	20	22.1	8.7	8.1	
13.91	8.0/22.0-15 M	215/40-15	80V	6.31	12119 A-60	303	7.0 TO 8.5	20	22.1	8.7	8.1	

Harder to —————> Softer
 A-33 A-29 A-60 A-31 A-30 A-24

Circuit = For circuit use and greater longevity

Sprint = For qualifying, cold weather and when it's difficult to get heat in the tyre.



Roger Kraus Racing

Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546
 Phone 510-582-5031 Order Line 800-510-7223

Avon CR28 Sport for 2020 "Special Order"

Soft Compound race and wet weather tire.

WT	CR28 Sport DOT	K.G.	Compound	Price	RIM SIZES	PSI	DIA	SEC	T.W.
16.67	185/60R13	7.56	3413M A29	166	5.5 - 6.0	30	21.7	7.4	6.3
16.67	185/60R14	7.56	3414M A29	174	5.5 - 6.0	30	22.7	7.4	5.3
20.00	195/50R15	9.07	4752 A29	176	6.5 - 7.0	30	23.0	8.6	7.3
18.89	205/50R15	8.57	4151 A29	183	6.0 - 6.5	30	22.7	7.8	6.0
17.55	205/60R13	7.96	4222 A29	192	6.0 - 6.5	30	22.6	7.7	6.3

