



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

January 2020

Radical Tires From Avon Racing

	Dry		RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
	Slick	Molded Wet						
Radical - SR3/SR8 Radials								
16.1	205/580R15 (16897S) 333	296	7.0-8.0	7.00	20	22.83	8.6	8.2
17.3	265/600R16 (16898S) 333	379	10.0-12.0	10.75	20	23.60	11.4	10.3
16.1	205/580R15 (14245) A-94 H.C.	392	7.0-8.0	7.00	20	22.83	8.6	8.2
17.3	265/600R16 (14243) A-94 H.C.	485	10.0-12.0	10.75	20	23.60	11.4	10.3
	205/580R15 (14783) A-15 H.C.	423	7.0-8.0	7.00	20	22.83	8.6	8.2
	265/600R16 (14782) A-15 H.C.	542	10.0-12.0	10.75	20	23.60	11.4	10.3
	205/580R15 (15515) W-532 Molded WET		7.0-8.0	7.00	20	22.83	8.6	8.2
	265/600R16 (15516) W-532 Molded WET		10.0-12.0	10.75	20	23.60	11.4	10.3
Radical 13" Radials								
13.2	195/530R13 (12419 A-53)	330	7.0-8.0	7.50	20	20.80	9.2	8.1
17.7	250/570R13 (14399 A-11)	413	9.0-11.0	10.00	20	22.60	11.4	9.7

Dry Compounds - Soft A-53 / Medium Soft A-11 & 333 / Medium A-514

Wet Compounds- Soft A-15 / Medium W-532

Hillclimb Compound A-15 and A-94 Slicks

Prices Subject To Change Without Notice