

Michelin Camber and Tire Pressure Recommendations.

P3 Recommendation as starting point

Front 30/65R18 S8L Med

Rear 31/71R18 S9L Hard

Preco tables for camber and pressure below. For performance, longevity and safety do NOT run the tires in the red zone.

Track use without banking

Maximum speed 320 KM - 198.8 Mph

Wheel size range (12.5 +/- .5)

Minimal cold pressure 1.4 Bar

Distance run 180 Km, 111 miles

Down Force 450Dan - 1012# D Force

Michelin Slick LMP3, 30/65-18 S8L, S9L				
Camber	1.9 Bar	2.0 Bar	2.1 Bar	2.2 Bar
-4	0	0	1	1
-3.5	0	1	2	2
-3.25	0	2	2	2
From -2.0-3.0	0	2	2	2

Track use without banking

Maximum speed 320 KM

Wheel size range (13.0 +/- .5)

Minimal cold pressure 1.3 Bar

Distance run 180 Km, 111 Miles

Down Force 660 Dan - 1484# D Force

Michelin Slick LMP3, 31/71-18 S8L, S9L					
Camber	1.8 Bar	1.9 Bar	2.0 Bar	2.1 Bar	2.2 Bar
-3.5	0	2	2	2	2
-3.25	0	2	2	2	2
-3.0	0	2	2	3	3
-2.75	0	2	2	3	3

Bar	Psi
1.0	14.50
1.1	15.95
1.2	17.40
1.3	18.85
1.4	20.31
1.5	21.76
1.6	23.21
1.7	24.66
1.8	26.11
1.9	27.56
2.0	29.01
2.1	30.46
2.2	31.91
2.3	33.36
2.4	34.81

Michelin Slick LMP3, 30/65-18 S8L, S9L				
Camber	27.6	29.01	30.46	31.91
-4	0	0	1	1
-3.5	0	1	2	2
-3.25	0	2	2	2
From -2.0-3.0	0	2	2	2

Michelin Slick LMP3, 31/71-18 S8L, S9L					
Camber	26.11	27.6	29.01	30.46	31.91
-3.5	0	2	2	2	2
-3.25	0	2	2	2	2
-3.0	0	2	2	3	3
-2.75	0	2	2	3	3