



# Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546  
 ph 1-510-582-5031 - 1-800-510-7223

### Avon Radial Ply

				Rim	Rim	AT			
W.T.	<u>Formula One Radial Ply</u>	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
18	245/640R13 (13247 A11)	475	Call	11-12.5	11.75	20	25.20	12.6	9.50
	245/640R13 (13248 A-15)	575	Call	11-12.5	11.75	20	25.20	12.6	9.50
20	270/660R13 (12242 A11)	CALL	Call	11-12.5	11.75	20	25.75	13.4	11.1
21	315/660R13 (11505 A11)	574	Call	13-15	13.75	20	25.75	15.0	12.3
23	370/660R13 (9845 A11)	610	Call	14-16	15.0	20	25.75	17.0	15.0
	370/660R13 (9848 A-15)	680	Call	14-16	15.0	20	25.75	17.0	15.0

### Avon Radial Ply

				Rim	Rim	AT			
W.T.	<u>F3000 Radial Ply</u>	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
17	240/600R13 (13919 A11) 10952W)	484	Call	11-13	12.0	20	23.80	12.4	9.5
22	330/620R13 (9482 A11) (6021W)	582	Call	14-16	15.0	20	24.45	15.9	13.5

### Avon Radial Ply

				Rim	Rim	AT			
W.T.	<u>INDY Car Radials</u>	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
18	275/635R15 (13797 A11) (15675 A222)	543	Call	11-13	10.0	20	25.30	11.9	10.7
22	350/72015 (12700 A11) (15676 A222)	641	Call	14-16	14.0	20	28.31	16.3	13.9

### Avon Radial Ply

				Rim	Rim	AT			
W.T.	<u>Formula Atlantic - INDY Lights</u>	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
15	240/600R15 (14188 A53) (16146 A333)	468	Call	10-12	10.0	20	23.70	11.0	9.4
21	330/60R15 (14189 A53) (16147 A333)	574	Call	14-16	14.0	20	24.40	15.5	13.9

### Avon Radial Ply

				Rim	Rim	AT			
W.T.	<u>Group C, IMSA</u>	Slick	Wets	Sizes	Used	PSI	Diam	Sec	T.W.
	300/650R17 (15586 A24)	552	Call	11-12.5	12.0	20	25.70	13.0	12.0
	300/650R18 (15205 A11) (15128 A545)	552	Call	11-12.5	12.0	20	25.70	13.0	12.0
	335/645R18 (14744 A11) (17511 A24)	569	Call	13-14	13.0	20	25.55	14.2	13.1
	335/645R18 (15984 A545)	569	Call	13-14	13.0	20	25.55	14.2	13.1
	365/720R18 (15360 A11 ) (17511 A24)	623	Call	14.5-16	14.5	20	28.39	15.9	14.4
	365/720R18 (15360) (15610 A545)	623	Call	14.5-16	14.5	20	28.39	15.9	14.4

### Avon Bias Ply

					Rim	Rim	AT			
W.T.	<u>Formula B. F2, Early Sports Racers</u>	Slick	Hist New	Hist Old	Sizes	Used	PSI	Diam	Sec	T.W.
15	9.1/21.0-13 (6428 A11)	343	408	418	8.5-10.5	10.0	20	21.0	10.9	9.1
19	12.0/23.0-13 (7239 A11)	397	482	492	12-14	13.0	20	23.2	14.5	12.3

### Avon Bias Ply

					Rim	Rim	AT			
W.T.	<u>Formula Atlantic - 2 liter Sports Racers</u>	Slick	Hist New	Hist Old	Sizes	Used	PSI	Diam	Sec	T.W.
9.3	9.0/20.0-13 (7210 A11) (15757 222)	325	390	400	8-10.5	10.0	20	20.0	10.6	9.2
20	13.0/23.0-13 7262 A11) (15760 222)	<u>410</u>	495	505	13-15	14.0	20	23.35	15.2	13.00

### Avon Bias Ply

					Rim	Rim	AT			
W.T.	<u>Sports Racers - Spec Applications</u>	Slick	Hist New	Hist Old	Sizes	Used	PSI	Diam	Sec	T.W.
12	7.0/21.0-13 (11452 A11)	306	361	371	6-8	8.0	20	20.6	9.0	7.2
17	9.2/22.0-13 (11453 A11)	329	394	404	8.5-10.5	10.0	20	22.4	11.1	9.1
9.3	7.0/20.0-13 Call for Compounds A11-222-007	290	345	355	6-8	6.0	20	20.4	7.6	7.4
11.3	8.2/22.0-13 Call For Compounds A11-222-007	315	380	390	8-10	8.0	20	22.0	9.7	8.6

### Avon Bias Ply

					Rim	Rim	AT			
W.T.	<u>Formula B- Historic &amp; Monoposto</u>	Slick	Hist New	Hist Old	Sizes	Used	PSI	Diam	Sec	T.W.
15	8.2/22.0-13 (3146 A11)	315	380	390	7-10	9.0	20	22.0	10.1	8.6
19	10.5/23.0-13 (4125 A11) Rear	397	472	482	9-11.5	11.0	20	23.5	12.3	10.3
15	9.1/21.0-13 (6428 A11)	343	408	418	8.5-10.5	10.0	20	21.0	10.9	9.1
19	12.0/23.0-13 (7239 A11)	397	482	492	12-14	13.0	20	23.2	14.5	12.3
20	13.0/23.0-13 7262 A11) (15760 222)	<u>410</u>	495	505	13-15	14.0	20	23.35	15.2	13.00
20	13.0/24.5-13 (6429 A11)	431	516	526	13-15	14.0	20	24.3	15.5	12.5

Hard      Avon Compounds      Medium      Very Soft      Super Soft  
 A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



# Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546  
 ph 1-510-582-5031 - 1-800-510-7223

## Avon Bias Ply

W.T.	Formula 1 & Other	Slick	Wets	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.5/16.0-10 (7340 A11) (10338 A15)	387	Call	8-9.5	9.0	20	15.9	9.3	8
	8.2/20.0-13 (2260 A11)(2555W)	306	Call	7-9	9.0	20	19.95	9.8	8.5
14	9.0/20.0-13 (7210 A11) (2553W)	325	Call	8-10.5	10.0	20	20.0	10.6	9.2
13	10.0/20.0-13 (2545 A11) (4134W)	343	Call	9-11	10.0	20	19.8	11.1	10.2
	10.0/20.0-13 (14763 A11 Kevlar)	343	Call	9-11	10.0	20	19.8	11.1	10.2
15	9.0/21.0-13 (4619 A15)	404	Call	8-10.5	10.0	20	21.0	10.9	9.1
15	9.0/21.0-13 (6428 A11)	343	Call	8-10.5	10.0	20	21.0	10.9	9.1
	10.0/21.0-13 (16577 A11) F1	348	Call	9-11	10.0	20	21.0	11.1	10.2
15	10.0/22.0-13 (9772 A15)	461	Call	9-12	11.0	20	22.1	11.9	10.3
15	10.0/22.0-13 (10358 A11)	349	Call	9-12	11.0	20	22.1	22.1	10.3
19	10.5/23.0-13 (2126 A11 Frt) (4125 A11 Rear)	397	Call	9-11.5	11.0	20	23.5	12.3	10.3
	10.5/23.0-13 (2594 A15 F1 Front)	397	Call	9-11.5	11.0	20	23.5	12.3	10.3
18	10.5/23.0-15 (3101 A11)	456	Call	9-12	11.0	30	23.55	12.0	10.3
21	13.0/24.5-13 (6429 A11)	431	Call	13-15	14.0	20	24.3	15.5	12.5
27	15.0/26.0-13 (2133 A11) (2595 A15)	526	Call	15-18	16.0	20	25.75	17.8	15
28	16.2/26.0-13 (3354 A11) (5347W)	559	Call	16-18	17.0	20	25.8	18.8	16.3

## Avon Bias Ply

W.T.	FIA - Can Am - USRRC - Other	Slick	Hist New	Hist Old	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.0/21.5-15 (14765 A11) (6881 A24) ( 123989 A56)	399	464	474	6.5-8.5	7.5	30	21.80	8.8	7.8
	8.0/21.5-15 (6881 A24)	399								
	8.7/21.5-15 (14754 A11) (6460 A24) (4871 A15)	433	498	508	7.5-9.5	8.0	30	22.10	9.7	8.4
	9.5/21.5-15 (4700 A24)	449	524	534	10.0	10.0	30	21.85	10.7	9.5
	9.5/21.5-15 (2829 A11) (3640 A15)	449	524	534	8-10	10.0	30	21.85	10.7	9.5
	10.7/21.5-15 (2036 A11) (2412 A15)	402	477	487	9-11	10.0	30	21.85	11.3	10.6
	10.7/21.5-15 (12417 A53) Kevlar	482	557	567	9-11	10.0	30	21.85	11.3	10.6
18	7.5/23.0-15 (5893 A24)	377	442	452	7-8.5	8.0	30	22.85	8.5	7.4
19	8.5/23.5-15 (6524 A24)	425	490	500	7-9.5	8.5	30	23.60	9.6	8.3
20	9.1/23.5-15 (6132 A11) (5978 A24)	440	505	515	8-9.5	8.5	30	23.55	9.9	9.1
18	10.5/23.0-15 (3101 A11)	456	531	541	9-12	11.0	30	23.55	12.0	10.3
18	10.5/23.0-15 4301 A24)	491	566	576	9-12	11.0	30	23.55	12.0	10.3
21	11.0/23.5-15 (3100 A11)	456	531	541	10-12	11.0	30	23.3	12.1	11.3
21	11.0/23.5-15 (4263 A24)	501	576	586	10-12	11.0	30	23.3	12.1	11.3
21	12.5/23.5-15 (2351 A11) (3733 A24)	522	607	617	11-13.5	12.0	30	23.3	13.3	12.7
21	9.5/25.0-15 (9928 A24) (14426 A11)	455	530	540	9-11	10.0	30	24.8	11.7	9.3
22	11.0/25.0-15 (4284 A24) (14427 A11)	473	548	558	10-12	12.0	30	24.7	13.6	11.3
24	13.0/25.0-15 (4319 A11)	505	590	600	11.5-14	14.0	30	24.8	15.4	13.2
24	13.0/25.0-15 (3731 A24)	580	665	675	11.5-14	14.0	30	24.8	15.4	13.2
27	15.0/26.0-15 (3127 A11) ( 4302 A24)	535	640	650	14-17	16.0	30	25.8	17.4	15
27	16.2/26.0-15 (3831 A11)	568	673	683	16-19	16.0	30	25.8	17.9	16.3
25	12.5/27.0-15 (4285 A24) (11764 A11)	476	561	571	11.5-14.5	13.0	30	27.0	15.3	12.5
27	14.0/27.0-15 (3358 A11) (4300 A24)	505	610	620	13-16	15.0	30	27.1	16.7	14
28	16.0/27.0-15 (3099 A11)	581	686	696	15-19	16.0	30	27.5	16.8	16.1
17	9.5/23.5-16 (3533 A24)	425	490	500	8.5-10.5	8.5	30	23.6	9.8	9.5
19	10.0/23.0-16 (11760 A11) (3742 A24)	455	530	540	10-12	10.0	30	23.6	11.1	10.3
18	11.0/23.5-16 (3131 A11)	473	548	558	10-12	11.0	30	23.6	12.6	11.3
18	11.0/23.5-16 (4172 A24)	504	579	589	10-12	11.0	30	23.6	12.6	11.3
18	11.0/23.5-16 (15111 A37)	504	579	589	10-12	11.0	30	23.6	12.6	11.3
22	11.0/25.0-16 (2992 A11) (5260 A37)	506	581	591	10-12	12.0	30	24.8	13.3	11.3
22	12.5/23.5-16 (3069 A11) (3831 A24 (3604 A15)	534	629	639	11-13.5	12.0	30	23.4	13.6	12.7
23	12.5/25.0-16 (4247 A11)	564	649	659	11.5-14	13.0	30	24.8	14.2	12.5
23	12.5/25.0-16 (4147 A24)	564	649	659	11.5-14	13.0	30	24.8	14.2	12.5
24	13.5/25.0-16 (11759 A11)	483	588	598	12-14.5	14.0	30	25.0	15.2	13.4
24	13.5/25.0-16 (3845 A24)	530	635	645	12-14.5	14.0	30	25.0	15.2	13.4
26	14.0/27.0-16 (2993 A11)	517	622	632	13-16	15.0	30	27.1	16.7	14.0
26	14.0/27.0-16 (15020 A24)	580	685	695	13-16	15.0	30	27.1	16.7	14.0

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



# Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546  
 ph 1-510-582-5031 - 1-800-510-7223

### Avon Radial Ply F.C., F1000, S2.

#### Formula Continental, S2 & F1000/FB Tires

	Slick			Rim	Rim	AT				
				Sizes	Used	PSI	Diam	Sec	T.W.	
175/530R13 (17614 222) FOR 2021	304			6-8	6.0	20	20.95	7.75	7.0	
200/565R13 (17615 222) FOR 2021	334			8-10	8.0	20	22.32	10.2	9.2	

### Avon Bias Ply - SCCA

#### Formula Continental, S2 & F1000/FB Tires

	Slick	Hist New	Hist Old	Rim	Rim	AT				
				Sizes	Used	PSI	Diam	Sec	T.W.	
9.3 7.0/20.0-13 (15502 007) (15763 222)	290	345	355	6-8	6.0	20	20.8	7.6	7.4	
11.3 8.2/22.0-13 (16479 007) (15766 222)	315	380	390	8-10	8.0	20	22.0	9.7	8.6	
9.2/22.0-13 (17810 007) NEW	329	394	404	8.5-10.5	10.0	20	22.4	11.1	9.1	

#### Formula Continental, S2 & F1000/FB WETS

				Sizes	Used	PSI	Diam	Sec	T.W.	
160/530R13 (13593 W561)	299	<b>Molded Wets</b>		5.5-7.5	6.0	20	20.9	7.4	6.3	
180/565R13 (13594 W561)	349	<b>Molded Wets</b>		5.5-8.5	7.0	20	22.1	8.7	7.2	

### SCCA Stohr, P1, P2, S.V and F.M.

				Sizes	Used	PSI	Diam	Sec	T.W.	
11.15 8.2/20.0-13 (16881 222)	306			7-9	9.0	20	19.95	9.8	8.5	
16.95 10.0/22.0-13 (16647 222)	345			9-12	11.0	20	22.1	11.9	10.3	
9.5 8.2/20.0-13 (17778 222) Light Wt	306			7-9	9.0	20	19.95	9.8	8.5	
14.9 10.0/22.0-13 (17779 222) Light Wt	345			9-12	11.0	20	22.1	11.9	10.3	
17 9.2/22.0-13 (17810 007) NEW	329	394	404	8.5-10.5	10.0	20	22.4	11.1	9.1	

#### F.A & 2 liter Sports Racers

				Sizes	Used	PSI	Diam	Sec	T.W.	
14 9.0/20.0-13 (7210 A11) ( 15757 222)	325	Call		8-10	9.0	20	20.0	10.6	9.2	
20 13.0/23.0-13 (7262 A11) (15760 222)	410	Call		13-15	14.0	20	23.25	15.2	13.0	

#### SCCA GT3, E Production

				Sizes	Used	PSI	Diam	Sec	T.W.	
17.5 9.0/23.3-15 (16972 A545)	336	Call		7.0-9.5	7.0	30	23.47	9.5	9.0	

### Avon Radial Ply F.A. Sports Racers

#### Norma, Wolf, DP02. Indy Lights

				Rim	Rim	AT				
				Sizes	Used	PSI	Diam	Sec	T.W.	
15 240/600R15 (14188 A53) (16146 333)	468	Call	Wets	10-12	10.0	20	23.7	11.0	9.4	
21 330/620R15 (14189 A53) (16147 333)	564	Call		14-16	14.0	20	24.4	15.5	13.3	

#### Special Application Radials

				Sizes	Used	PSI	Diam	Sec	T.W.	
11.9 175/530R13 Spec Order	Call	Call	Wets	6.5-7.5	7.0	20	20.9	8.0	7.1	
180/550R13 (15615 007)	379	Call		8.5-9.5	9.0	20	21.8	9.5	7.3	
13.2 195/530R13 Special Order	Call	Call		8-9	8.5	20	20.8	9.7	8.1	
14 210/550R13 (15485 007) ( 16287 333)	383	Call		9-10	10.0	20	21.8	10.6	8.3	
<b>14 210/550R13 (17741 222 NEW 2021)</b>	<b>383</b>	<b>Call</b>		<b>9-10</b>	<b>10.0</b>	<b>20</b>	<b>21.8</b>	<b>10.6</b>	<b>8.3</b>	
14 210/550R13 WET (16810) CR71	420	Wets		9-10	10.0	20	21.8	10.6	8.3	
15.6 230/550R13 (15505 007) (16069 222) ( 16988 333)	411	Call		9-11	10.0	20	21.8	11.4	9.2	
17.7 250/570R13 (15616 007) (7941 333)	442	Call		9-11	10.0	20	22.6	11.4	9.7	
<b>17.7 250/570R13 (174742 222 NEW 2021)</b>	<b>442</b>	<b>Call</b>		<b>9-11</b>	<b>10.0</b>	<b>20</b>	<b>22.6</b>	<b>11.4</b>	<b>9.7</b>	
17.7 250/570R13 (15261 W534)	464	Wets		9-11	10.0	20	22.6	11.4	9.7	
290/570R13 WET (17551) CR71	474	Wets		10.5-12.5	11.75	20	22.8	12.5	11.1	
16.6 290/570R13 (15714 007) (16288 333)	445	Call		10.5-12.5	11.75	20	22.8	12.5	11.1	
<b>16.6 290/570R13 (17743 222 NEW 2021)</b>	<b>445</b>	<b>Call</b>		<b>10.5-12.5</b>	<b>11.75</b>	<b>20</b>	<b>22.8</b>	<b>12.5</b>	<b>11.1</b>	
18.4 300/600R13 (15506 007) (16070 222) ( 16989 333)	446	Call		13-14	13.0	20	23.9	14.7	11.9	

#### W.T. Formula Atlantic - INDY Lights

	Slick	Wets		Sizes	Used	PSI	Diam	Sec	T.W.	
15 240/600R15 (14188 A53) (16146 A333)	468	Call		10-12	10.0	20	23.70	11.0	9.4	
21 330/620R15 (14189 A53) (16147 A333)	574	Call		14-16	14.0	20	24.40	15.5	13.3	

**Hard Avon Compounds Medium Very Soft Super Soft**

**A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063**

Prices Subject To Change Without Notice!



# Roger Kraus Racing Ent, Inc.

2896 Grove Way, Castro Valley, Calif 94546  
 ph 1-510-582-5031 - 1-800-510-7223

## Road Race - Avon Bias Ply Medium Soft

### Autocrossing Compounds - Not Super Soft

	Slick	Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
8.5/16.0-10 (7340 A11)	354	8-9.5	9.0	20	15.9	9.3	8.0
7.0/20.0-13 (10992 A11)	262	6-8	6.0	20	20.8	7.6	7.4
7.0/21.0-13 (11452 A11)	304	6-8	8.0	20	20.6	9	7.2
8.2/20.0-13 (2260 A11)	306	7-9	9.0	20	19.95	9.8	8.5
9.0/20.0-13 (7210 A11)	325	8-10.5	10	20	20.0	10.6	9.2
10.0/20.0-13 (2545 A11)	343	9-11	10	20	19.8	11.1	10.2
10.0/20.0-13 (14763 A11) Kevlar	343	9-11	10	20	19.8	11.1	10.2
9.0/21.0-13 (6428 A11)	343	8-10.5	10.0	20	10.9	9.1	9.1
10.0/21.0-13 (16577 A11) F1	342	9-11	10	20	21.0	11.1	10.2
8.2/22-13 (3146 A11)	315	7-9	9.0	20	22.0	10.1	8.6
8.2/20.0-13 (10993 A11)	315	8-10	8.0	20	22.0	9.7	8.6
9.2/22.0-13 (11453 A11)	329	8.5-10.5	10.0	20	22.4	11.1	9.1
10.0/22.0-13 (10358 A11)	349	9-12	11.0	20	22.1	11.9	10.3
10.5/23.0-13 (2126 A11) F1 Front	397	9-11.5	11.0	20	23.5	12.3	10.3
10.5/23.0-13 (4125 A111) Rear Use	397	9-11.5	11.0	20	23.5	12.3	10.3
12.0/23.0-13 (7239 A11)	397	12-14	13.0	20	23.2	14.5	12.3
13.0/23.0-13 (7262 A11)	410	13-15	14.0	20	23.25	15.2	13.0
13.0/24.5-13 ( 6429 A11)	431	13-15	14.0	20	24.3	15.5	12.5
15.0/26.0-15 (2133 A11)	526	15-18	16.0	20	25.8	17.8	15
16.2/26.0-13 (3354 A11)	559	16-18	17.0	20	25.8	18.8	16.3
8.0/21.5-15 (14765 A11) (6881 A24)	399	6.5-8.5	7.5	30	21.8	8.8	7.8
8.7/21.5-15 (14754 A11) ( 6460 A24)	433	7.5-9.5	8.0	30	22.1	9.7	8.4
9.5/21.5-15 (4700 A24)	449	8-10	10.0	30	21.85	10.7	9.5
9.5/21.5-15 (2829 A11) (3640 A15)	449	8-10	10.0	30	10.7	9.5	9.5
10.0/21.5-15 (14766 A11)	455	8.5-11	10.0	22	22.0	10.94	9.53
10.7/21.5-15 (2036 A11) (2412 A15)	482	9-11	10.0	30	21.85	11.3	10.6
7.5/23.5-15 (5983 A24)	377	7-8.5	8.0	30	22.8	8.5	7.4
8.5/23.5-15 (6524 A24)	425	7-9.5	8.5	30	23.6	9.6	8.3
9.1/23.5-15 (6132 A11) ( 5978 A24)	440	8-9.5	8.5	30	23.55	9.9	9.1
10.5/23.0-15 (3101 A11)	456	9-12	11.0	30	23.55	12.0	10.3
10.5/23.0-15 (4301 A11)	491	9-12	11.0	30	23.55	12.0	10.3
11.0/23.5-15 (3100 A11)	456	10-12	11.0	30	23.3	12.1	11.3
11.0/23.5-15 (4263 A24)	500	10-12	11.0	30	23.3	12.1	11.3
12.5/23.5-15 (2351 A11)	522	11-13.5	10.0	30	23.3	13.3	12.7
9.5/25.0-15 (9928 A24) ( 14426 (A11)	455	9-11	10.0	30	24.8	11.7	9.3
11.0/25.0-15 ( 4284 A24) ( 14427 A11)	473	10-12	12.0	30	24.7	13.6	11.3
13.0/25.0-15 (4319 A11)	505	11.5-14	14.0	30	24.8	15.4	13.2
13.0/25.0-15 (3731 A24)	580	11.5-14	14.0	30	24.8	15.4	13.2
15.0/26.0-15 (3127 A11) ( 4302 A24)	535	14-17	16.0	30	25.8	17.4	15
16.2/26.0-15 (3831 A11)	568	16-19	16.0	30	25.8	17.9	16.3
12.5/27.0-15 4285 A24) (11764 A11)	476	11.5-14.5	13.0	30	27.0	15.3	12.5
14.0/27.0-15 (3358 A11) (4300 A24)	505	13-16	15.0	30	27.1	16.7	14.0
16.0/27.0-15 (3099 A11)	581	15-19	16.0	30	27.5	16.8	16.1
10.0/23.5-16 (11760 A11) (3742 A24)	455	10-12	10.0	30	23.6	11.1	10.3
11.0/23.5-16 (3131 A11)	473	10-12	11.0	30	23.6	12.6	11.3
11.0/23.5-16 (4172 A24)	504	10-12	11.0	30	23.6	12.6	11.3
11.0/25.0-16 (2992 A11) (5260 A37)	506	10-12	11.0	30	24.8	12.6	11.3
12.5/25.0-16 (4247 A11)	564	10-12	11.0	30	24.8	12.6	11.3
12.5/25.0-15 (4147 A24)	564	10-12	11.0	30	24.8	12.6	11.3
12.5/27.0-16 (15006 A24)	CALL	11.5-14	13.0	30	27.0	15.3	12.5
13.5/25.0-16 ( 11759 A11)	483	12-14.5	14.0	30	25.0	15.2	13.4
13.5/25.0-16 ( 3845 A24)	530	12-14.5	14.0	30	25.0	15.2	13.4
14.0/27.0-15 ( 2993 A11)	517	13-16	15.0	30	27.1	16.7	14.0
14.0/27.0-16 15020 A24)	580	13-16	15.0	30	27.1	16.7	14.0

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice!



Note: The A15 is a Hill Climb, Autocrossing and a Wet use tire. For wet use we hand grove these tires in house. These tires have more tread depth compared to other slicks. 9-21-2021

**Avon Bias Ply  
Very Soft to Super Soft Tires**

These Tires can be Hand Cut into wets

**10-13"**

7.0/16.0-10 (13758 A15)
8.5/16.0-10 (10338 A15)
8.2/20.0-13 (2555 A15)
8.2/22.0-13 (14209 A15)
9.0/20.0-13 (2553 A15)
9.0/21.0-13 (4619 A15)
10.0/20.0-13 (4134 A15)
10.0/22.0-13 (9772 A15)
10.5/23.0-13 (2594 A15 Rec Front)
10.5/23.0-13 (4864 A15 Rec Rear)
12.0/23.0-13 (2888 A15)
13.0/23.0-13 (2391 A15)
15.0/26.0-13 (2595 A15)
16.2/26.0-13 (5347 A15)

**15"**

8.0/21.5-15 (4867 A15 6 Ply)
8.7/21.5-15 (4871 A15)
9.5/21.5-15 (3640 A15)
10.0/21.5-15(3503 A15)
10.7/21.5-15 (2412 A15)
8.5/23.5-15 (9318 A15)
9.1/23.5-15 (5602 A15)
10.5/23.0-15 (3283 A15)
11.0/23.5-15 (3284 A15)
11.0/25.0-15 (2459 A15)
13.0/25.0-15 ( 2424 A15)
15.0/26.0-15 (3286 A15)
12.5/27.0-15 ( 2253 A15)
16.0/27.0-15 (3593 A15)

**16"**

8.5/23.3-16 (9806 A15)
9.5/21.5-16 (3647 A15)
10.0/23.5-16 (3106 A15)
11.0/23.5-16 (2458 A15)
11.0/25.0-16 (2994 A15)
12.5/23.5-16 (3604 A15)
12.5/25.0-16 (12866 A15)
13.5/25.0-16 (4116 A15)
14.0/27.0-16 (2995 A15)

**Avon Bias Ply - Road Race, Auto X, H.C & Wet.  
Autocrossing - Soft to Super soft Tires**

				Rim	Rim	AT			
	Slick	INT.	WET	Sizes	Used	PSI	Diam	Sec	T.W.
	299	Call	Call	6.5-8	7.5	20	15.9	7.8	7.0
	387	Call	Call	8-10.5	9	20	15.9	9.3	8.0
	306	Call	Call	7-9	9	20	20.0	9.8	8.5
	395	Call	Call	7-10	9	20	22.0	10.1	8.6
	321	Call	Call	8-10.5	10	20	20.0	10.6	9.2
	404	Call	Call	8-10.5	10	20	20.9	9.1	9.1
	343	Call	Call	9-11	10	20	19.8	11.1	10.2
	461	Call	Call	9-12	11	20	22.1	11.9	10.3
	389	Call	Call	9-11.5	11	20	23.5	12.3	10.3
	458	Call	Call	9-11.5	11	20	23.5	12.3	10.3
	527	Call	Call	12-14	10	20	23.2	14.5	12.3
	529	Call	Call	13-15	14	20	23.3	15.2	13.0
	526	Call	Call	15-18	16	20	25.8	17.8	15.0
	643	Call	Call	16-18	17	20	25.8	18.8	16.3
	399	Call	Call	6.5-8.5	7.5	30	21.8	8.8	7.8
	423	Call	Call	7.5-9.5	8	30	22.1	9.7	8.4
	439	Call	Call	8-10	10	30	21.9	10.7	9.5
	445	Call	Call	8.5-11	10	30	21.9	11	10.0
	394	Call	Call	9.11	10	30	21.9	11.3	10.6
	427	Call	Call	7.5-9.5	8.5	30	23.6	9.6	8.5
	430	Call	Call	8-9.5	8.5	30	23.6	9.9	8.8
	449	Call	Call	10-12	11	30	23.55	12	10.3
	450	Call	Call	11-12	11	30	23.0	12.1	11.3
	498	Call	Call	10-12	12	30	24.7	13.6	11.3
	570	Call	Call	11.5-14	14	30	24.8	15.4	13.2
	535	Call	Call	14-17	16	30	25.8	17.4	15.0
	564	Call	Call	13-16	15	30	27.1	15.2	12.5
	651	Call	Call	15-19	16	30	27.5	16.8	16.1
	436	Call	Call	7.5-8	8	30	23.6	9.6	8.8
	466	Call	Call	8.5-10.5	8.5	30	23.6	9.8	9.5
	478	Call	Call	9-11	10	30	23.6	11.1	10.0
	473	Call	Call	10-12	12	30	23.5	12.6	11.3
	469	Call	Call	10-12	12	30	24.8	13.3	11.3
	524	Call	Call	11.5-13.5	13.75	30	23.4	13.8	12.7
	554	Call	Call	11.5-13.5	13	30	24.8	14.2	12.5
	483	Call	Call	12-14.5	14	30	25.0	15.2	13.4
	511	Call	Call	13-16	14	30	27.2	15.8	14.0

**Super Soft Tires**

Avon Bias Ply - Auto X, H.C & Wet  
Auto X, H.C., A92 Comp. - Super Soft

				Rim	Rim	AT			
	Slick	INT.	WET	Sizes	Used	PSI	Diam	Sec	T.W.
7.2/20.0-13 (14254 A92)	339	Call	Call	6-8	8.0	20	20.2	9	7.1
8.2/20.0-13 (14140 A92)	358	Call	Call	7-9	9.0	20	20.0	9.75	8.5
9.0/20.0-13 (14143 A92)	369	Call	Call	8-10	10.0	20	20.0	10.65	9.2
10.0/20.0-13 (14251 A92)	392	Call	Call	9-11	10.0	20	19.8	11.1	10.2
7.0/21.0-13 ( 14207 A92)	349	Call	Call	6-8	8.0	20	20.6	9	7.2
8.5/21.5-13 (14176 A92)	392	Call	Call	7.5-9	9.0	20	20.8	10.2	8.5
9.0/21.0-13 (14177 A92)	392	Call	Call	8-10	10.0	20	21.0	10.9	9.1
9.2/22.0-13 (14142 A92)	435	Call	Call	8.5-10.5	10.0	20	22.4	11.1	9.1

Hard Avon Compounds Medium Very Soft Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063

Prices Subject To Change Without Notice.! 9/2021