



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

Avon Radial Ply		Tread Pattern								
WT	Formula 1, Radial	Slick	Wets	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
18	245/640R13 F1 (13247-A11) (13248W)	430	Call	11.0 TO 12.5	11.75	20	25.20	12.6	9.5	
20	270/660R13 (12242 A-11)	569	Call	11.0 TO 12.5	11.75	20	25.70	13.4	11.1	
21	315/660R13 F1 (11505-A11) (9847W)	561	Call	13.0 TO 15.0	13.75	20	25.75	15.0	12.3	
23	370/660R13 F1 (9845-A11) (9848W)	597	Call	14.0 TO 16.0	15.00	20	25.75	17.0	15.0	
F3000, Radial		Slick	Wets	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
17	245/600R13 (13919A11)(10952W)	438	Call	11.0 TO 13.0	12.00	20	23.8	12.4	9.5	
22	330/620R13 (9482-A11)(6021W)	557	Call	14.0 TO 16.0	15.00	20	24.45	15.9	13.5	
Indy Car		Slick	Wets	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
18	275/635R15 (13797-A11)(15675 A222)	530	Call	11.0 TO 13.0	10.00	20	25.30	11.9	10.7	
26	350/720R15 (12700-A11) (15676 A222)	628	Call	14.0 TO 16.0	14.00	20	28.31	16.3	13.9	
Formula Atlantic - Indy Lights		Slick	Wets	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
15	240/600R15 (14188-A53) (16868 A22)	455	Call	10.0 TO 12.0	10.00	20	23.70	11.0	9.4	
21	330/620R15 (14189-A53) (16867 A222)	531	Call	14.0 TO 16.0	14.00	20	24.40	15.5	13.3	
Avon Radial Group C										
	300/650R17 (15586 A24)	577	CALL	11.0 TO 12.5	12.0	20	25.70	13.0	12.0	
	300/650R18 (15205 A11) (15407 A24)	594	CALL	11.0 TO 12.5	12.0	20	25.70	13.0	12.0	
	335/645R18 (14744 A11)(15984 A545)	621	CALL	13.0 TO 14.0	13.0	20	25.55	14.2	13.1	
	365/720R18 (15360 A11)(15610 A545)	644	CALL	14.5 TO 16.0	14.50	20	28.39	15.9	14.4	
Avon Bias Ply		Tread Pattern								
Formula B/Formula 2/F.A. & 2 Liter Sports Racers		Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
WT	9.0/20.0-13 (7210-A11)	282	347	357	8.0 TO 10.5	10.00	20	20.00	10.6	9.2
14	12.0/23.0-13 (7239A11)	375	460	470	12.0 TO 14.0	13.00	20	23.20	14.5	12.3
19	13.0/23.0-13 (7262-A11)	392	477	487	13.0 TO 15.0	14.00	20	23.25	15.2	13.0
20										
Formula B/Formula 2/F.A. & 2 Liter Sports Racers		Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
WT	9.0/20.0-13 (15757-222)	290	355	365	8.0 TO 10.5	10.00	20	20.00	10.6	9.2
9.3	13.0/23.0-13 (15760-222)	399	474	484	13.0 TO 15.0	14.00	20	23.25	15.2	13.0
11.3										
Sports Racers / Special Application		Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
WT	7.0/21.0-13 (11452 A-11)	266	321	331	6.0 TO 8.0	8.00	20	20.60	9.0	7.2
12	9.2/22.0-13 (11453 A-11)	312	377	387	8.5 TO 10.5	10.00	20	22.40	11.1	9.1
17										
Sports Racers / Special Application		Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
WT	7.0/20.0-13 (115763-222)	248	303	313	6.0-8.0	6.00	20	20.80	7.6	7.4
NEW 10	8.2/22.0-13 (157664-222)	293	358	368	8.0-10.0	8.00	20	22.00	9.7	8.6
NEW 12										
Formula B - Historic & Monoposto		Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
15	8.2/22.0-13 (3146-A11)	298	363	373	7.0 TO 10.0	9.00	20	22.00	10.1	8.6
19	10.5/23.0-13 (4125-A11)(2126-A11)	377	452	462	9.0 TO 11.5	11.00	20	23.50	12.3	10.3
15	9.0/21.0-13 (6428-A11)	300	365	375	8.0 TO 10.5	10.00	20	21.00	10.9	9.1
19	12.0/23.0-13 (7239-A11)	375	460	470	12.0 TO 14.0	13.00	20	23.20	14.5	12.3
20	13.0/23.0-13 (7262-A11)	392	477	487	13.0 TO 15.0	14.00	20	23.25	15.2	13.0
19	13.0/24.5-13 (6429-A11)	407	492	502	13.0 TO 15.0	14.00	20	24.30	15.5	12.5
21										
Formula 1, Bias Ply		Slick	Wets	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
	8.5/16.0-10 (7340-A11)(10338 A15)	339	Call	8.0 TO 9.5	9.00	20.0	15.9	9.3	8.0	
	8.2/20.0-13 (2260-A11) (2555W)	265	Call	7.0 TO 9.0	9.00	20	19.95	9.8	8.5	
14	9.0/20.0-13 (7210-A11) (2553W)	282	Call	8.0 TO 10.5	10.00	20	20.00	10.6	9.2	
13	10.0/20.0-13 (2545-A11) (4134W)	300	Call	9.0 TO 11.0	10.00	20	19.80	11.1	10.2	
New	10.0/20.0-13 (2545-A11) Kevlar	300	Call	9.0 TO 11.0	10.00	20	19.80	11.1	10.2	
New	10.0/21.0-13 (16577 -A11) F-1	335	Call	9.0 TO 11.0	10.00	20	21.00	11.1	10.2	
15	10.0/22.0-13 (9772 A15)	406	Call	9.0 TO 12.0	11.00	20	22.10	11.9	10.3	
15	10.0/22.0-13 (10358-A11)	328	Call	9.0 TO 12.0	11.00	20	22.10	11.9	10.3	
15	9.0/21.0-13 (4619S A15)	356	Call	8.0 TO 10.5	10.00	20	21.00	10.9	9.1	
15	9.0/21.0-13 (6428-A11) (4619W)	300	Call	8.0 TO 10.5	10.00	20	21.00	10.9	9.1	
19	0.5/23.0-13 (2126-A11) (4125 A11Rear)(2594 A15)	375	Call	9.0 TO 11.5	11.00	20	23.50	12.3	10.3	
21	13.0/24.5-13 (6429-A11) (6542 A15)	407	Call	13.0 TO 15.0	14.00	20	24.30	15.5	12.5	
27	15.0/26.0-13 (2133-A11) (2595 A15)	499	Call	15.0 TO 18.0	16.00	20	25.75	17.8	15.0	
28	16.2/26.0-13 (3354-A11) (5347W)	533	Call	16.0 TO 18.0	17.00	20	25.80	18.8	16.3	

* F-1 Spec Compound is A-11

F-1 Rain Tires are stocked in the more popular sizes.

Prices Subject to change without notice



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

	<u>FIA / Can-Am / USRRC</u>	Slick	Historic	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
	8.0/21.5-15 (14765-A-11)(6881-A24)(12389-A56)	342	407	417	6.5 TO 8.5	7.50	30.0	21.8	8.8	7.8
	8.7/21.5-15 (14754 A11) (6460 A24) (4871 A15)	374	439	449	7.5 TO 9.5	8.00	30	22.10	9.7	8.4
	9.5/21.5-15 (4700-A24)	350	425	435	8.0-10.0	10.00	30	21.85	10.7	9.5
	9.5/21.5-15 (2829-A11) (3640 A15)	395	470	480	8.0-10.0	10.00	30	21.85	10.7	9.5
	10.7/21.5-15 (2036 A-11) (2412 A15)	365	440	450	9.0-11.0	10.00	30	21.85	11.3	10.6
	10.7/21.5-15 (12417) A-53 Kevlar	398	473	483	9.0-11.0	10.00	30	21.85	11.3	10.6
18	7.5/23.0-15 (5983-A24)	340	405	415	7.0 TO 8.5	8.00	30	22.80	8.5	7.4
19	8.5/23.5-15 (6524-A24)	385	450	460	7.0 TO 9.5	8.50	30	23.60	9.6	8.3
20	9.1/23.5-15 (6132-A11)(5978 A24)	399	464	474	8.0 TO 9.5	8.50	30	23.55	9.9	9.1
18	10.5/23.0-15 (3101-A11)	413	488	498	9.0 TO 12.0	11.00	30	23.55	12.0	10.3
18	10.5/23.0-15 (4301 A24)	446	521	531	9.0 TO 12.0	11.00	30	23.55	12.0	10.3
21	11.0/23.5-15 (3100-A11)	413	488	498	10.0 TO 12.0	11.00	30	23.30	12.1	11.3
21	11.0/23.5-15 (4263-A24)	486	561	571	10.0 TO 12.0	11.00	30	23.30	12.1	11.3
21	12.5/23.5-15 (2351 A-11)(3733 A-24)	465	550	560	11.0 TO 13.5	12.00	30	23.30	13.3	12.7
21	9.5/25.0-15 (9928-A24) (14426S-A11)	413	488	498	9.0 TO 11.0	10.00	30	24.80	11.7	9.3
22	11.0/25.0-15 (4284-A24) (14427-A11)	442	517	527	10.0 TO 12.0	12.00	30	24.70	13.6	11.3
24	13.0/25.0-15 (4319-A11)	460	545	555	11.5 TO 14.0	14.00	30	24.80	15.4	13.2
24	13.0/25.0-15 (3731A-24)	509	594	604	11.5 TO 14.0	14.00	30	24.80	15.4	13.2
27	15.0/26.0-15 (3127-A11)(4302A-24)	516	621	631	14.0 TO 17.0	16.00	30	25.80	17.4	15.0
27	16.2/26.0-15 (3831-A11)	549	654	664	16.0 TO 19.0	16.00	30	25.80	17.9	16.3
25	12.5/27.0-15 (4285-A24)(11764-A11)	465	550	560	11.5 TO 14.5	13.00	30	27.00	15.3	12.5
27	14.0/27.0-15 (3358-A11)(4300-A24)	470	575	585	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
28	16.0/27.0-15 (3099-A11)	531	636	646	15.0 TO 19.0	16.00	30	27.50	16.8	16.1
17	9.5/23.3-16 (3533-A24)	385	450	460	8.5 TO 10.5	8.50	30	23.60	9.8	9.5
19	10.0/23.5-16 (11760-A-11) (3742-A24)	413	488	498	10.0 TO 12.0	10.00	30	23.60	11.1	10.3
17.72	11.0/23.5-16 (3131 A-11)	430	505	515	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (4172 A-24)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (15111 A-37)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
22	11.0/25.0-16 (2992-A11)(5260 A37)	460	535	545	10.0 TO 12.0	12.00	30	24.75	13.3	11.3
22	12.5/23.5-16(3069 A-011)(3081 A-24)(3604 A-15)	487	545	555	11.0 TO 13.5	12.00	30	23.40	13.8	12.7
23	12.5/25.0-16 (4247 A11)	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
22	12.5/25.0-16 (4147-A-24) 4PLY	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
27	12.5/27.0-16 (15006 A-24)	501	586	596	11.5 TO 14.5	13.00	30	27.00	15.3	12.5
24	13.5/25.0-16 (11759) A-11	474	579	589	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
24	13.5/25.0-16 (3845) A-24	519	624	634	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
26	13.2/27.0-16 (15013) A-24	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2
26	13.2/27.0-16 (15105) A-37	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2
26	14.0/27.0-16 (2993) A-11	471	576	586	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (15020) A-24	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (10774) A-37	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0

Note: In many sizes only the spec # shown is at that price. The price may be higher for alternate numbers or compounds!

The A-24 compound is one range harder than A-11. Most but not all Wets are A-15.

Prices Subject To Change Without Notice

Prices Subject to change without notice



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

NEW - Avon 16" Bias Ply Tires for 2019.

	Recommended for Porsche Club Cars.	Slick	Historic	Historic Old						
19	10.0/23.5-16 (11760-A-11) (3742-A24)	413	488	498	10.0 TO 12.0	10.00	30	23.60	11.1	10.3
17.72	11.0/23.5-16 (3131 A-11)	430	505	515	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (4172 A-24)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (15111 A-37)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
22	11.0/25.0-16 (2992-A11)(5260 A37)	460	535	545	10.0 TO 12.0	12.00	30	24.75	13.3	11.3
22	12.5/23.5-16(3069 A-011)(3081 A-24)(3604 A-15)	487	545	555	11.0 TO 13.5	12.00	30	23.40	13.8	12.7
23	12.5/25.0-16 (4247 A11)	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
22	12.5/25.0-16 (4147-A-24) 4PLY	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
27	12.5/27.0-16 (15006 A-24)	501	586	596	11.5 TO 14.5	13.00	30	27.00	15.3	12.5
24	13.5/25.0-16 (11759) A-11	474	579	589	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
24	13.5/25.0-16 (3845) A-24	519	624	634	12.0 TO 14.5	14.00	30	25.00	15.2	13.4

	Recommended for BMW 3.0 CSI and like cars.				RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
17.72	11.0/23.5-16 (3131 A-11)	430	505	515	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (4172 A-24)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (15111 A-37)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
22	11.0/25.0-16 (2992-A11)(5260 A37)	460	535	545	10.0 TO 12.0	12.00	30	24.75	13.3	11.3
23	12.5/25.0-16 (4247 A11)	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
22	12.5/25.0-16 (4147-A-24) 4PLY	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
24	13.5/25.0-16 (11759) A-11	474	579	589	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
24	13.5/25.0-16 (3845) A-24	519	624	634	12.0 TO 14.5	14.00	30	25.00	15.2	13.4

	Recommended for Porsche 935 run in the USA				RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
17.72	11.0/23.5-16 (3131 A-11)	430	495	505	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (4172 A-24)	445	520	530	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (15111 A-37)	474	549	559	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
26	14.0/27.0-16 (2993) A-11	471	576	586	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (15020) A-24	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (10774) A-37	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0

	Recommended for GT1 and Trans Am using 16x12.0" wide wheels.				RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
23	12.5/25.0-16 (4247 A11)	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
26	13.2/27.0-16 (15013) A-24	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2
26	13.2/27.0-16 (15105) A-37	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2

Compound Range

Very Soft	A-15	Wet Compound, Auto Crossing and cut for wet use.
Soft	A-11	Auto Crossing, Road Racing and cut for wet use.
Medium -	A-24	Road Racing, Auto Crossing.
Medium +	A-37	Road Racing, better durability than A24. Similar Temp Range.
Med Hard	A-60	Back up compound for A-37
Hard	A-29	Hard, enduro / long distance running

Prices Subject to change without notice

NEW - Avon Radical Tires for 2019

#	Newly updated Avon Radical Tires				RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
16.2	205/580R15 16987S 333 Dry Use	280			7.0 TO 8.0	7.00	29	22.80	8.6	8.2
17.6	265/600R16 16898S 333 Dry Use	360			10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.8	205/580R15 15515 WM W534 WET USE	304			7.0 TO 8.0	7.00	29	22.80	8.6	8.2
21.9	265/600r16 15516WM W534 WET USE	386			13.0 TO 16.0	15.00	30	27.10	16.7	14.0

These new Avon Radical tires are made in the new 333 compound which is very similar to the very successful Avon 222 compounds which hold track records at most of the west coast race tracks. The 333 compound requires less time to warm up the tires compared to Avon's 222 and 007 compounds while providing the same level of performance. You can expect minimal drop off in performance when racing and usually more usable track sessions before replacing the tires becomes an issue compared to most other brands.



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

F.C. Tires for 2019

WT	Formula Continental Bias Ply Dry Use	Slick	Historic New	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
9.3	7.0/20.0-13 (15502S A007)	251	306	316	6.0-8.0	6.00	20	20.80	7.6	7.4
11.3	8.2/22.0-13 (16479 A007)	295	360	370	8.0-10.0	8.00	20	22.00	9.7	8.6
9.3	7.0/20.0-13 (15763-222)	251	306	316	6.0-8.0	6.00	20	20.80	7.6	7.4
11.3	8.2/22.0-13 (15766-222)	295	360	370	8.0-10.0	8.00	20	22.00	9.7	8.6
Compounds = A007 Medium and A2222 Medium Soft										
WT	F.F.and F.C. Wet Use - Radials		Wets		RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
12.8	160/530R13 13593 W561)	262	Molded Wet		5.5-6.5	6.00	20	20.90	7.4	6.3
15.4	180/565R13 (13594 W561)	335	Molded Wet		5.5-8.5	7.00	20	22.38	8.7	7.2
WT	SCCA Stohr P-1-P-2 Bias Ply 222		Wets							
10	8.2/20.0-13 (16646-222) (16881-222)	276	Call		7.0 TO 9.0	9.00	20	19.95	9.8	8.5
14	10.0/22.0-13 (16647-222)	337	Call		9.0 TO 12.0	11.00	20	22.10	11.9	10.3
WT	Formula Atlantic - Sports Racer 222	Slick	Wet		RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
14	9.0/20.0-13 (15757-222)	290	Call		8.0 TO 10.5	10.00	20	20.00	10.6	9.2
20	13.0/23.0-13 (15760-222)	399	Call		13.0 TO 15.0	14.00	20	23.25	15.2	13.0
WT	SCCA - GT3, EP									
17.5	9.0/23.3-15 (16972 A545)	325			7.0 TO 9.5	7.00	30	23.47	9.5	9.0
This tire has a one inch narrower cross section on a 7.0" wide wheel than the Goodyear and Hoosier.										
WT	Formula Atlantic 15" Radials	Slick	Wet		RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
15	240/600R15 (14188-A53) (16868S 222)	455	Call		10.0 TO 12.0	10.00	20	23.70	11.0	9.4
21	330/620R15 (14189-A53) (16867S 222)	531	Call		14.0 TO 16.0	14.00	20	24.40	15.5	13.3
WT	Special Applications Radials	Slick	Wet		RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
11.9	175/530R13 (14279 A-53)(14315 A-15)	318	Call		6.5-7.5	7.00	20	20.90	8.0	7.1
	180/550R13 (11530 A11) (15909 222)	323	Call		8.5 - 9.5	9.00	20	21.80	9.5	7.3
13.2	195/530R13 (8419 A-53)(15853 007)	330	Call		8.0-9.0	8.50	20	20.80	9.7	8.1
14.0	210/550R13 (15485 007)	356	Call		9.0-10.0	10.00	20	21.80	10.6	8.3
14.0	210/550R13 (11380 A11)	356	Call		9.0-10.0	10.00	20	21.80	10.6	8.3
14.0	210/550R13 (14734 W561)	395	Wet		9.0-10.0	10.00	20	21.80	10.6	8.3
15.6	230/550R13 (11851 A53)	404	Call		9.0-11.0	10.00	20	21.80	11.4	9.2
15.6	230/550R13 (15505 007)	404	Call		9.0-11.0	10.00	20	21.80	11.4	9.2
15.6	230/550R13 (16969 222)	404	Call		9.0-11.0	10.00	20	21.80	11.4	9.2
15.6	230/550R13 (16988 333)	404	Call		9.0-11.0	10.00	20	21.80	11.4	9.2
17.7	250/570R13 (14399 A11) (15371 A545)	413	Call		9.0-11.0	10.00	20	22.60	11.4	9.7
17.7	250/570R13 (15616 007)	413	Call		9.0-11.0	10.00	20	22.60	11.4	9.7
17.7	250/570R13 (15261 W534)	444	Wet		9.0-11.0	10.00	20	22.60	11.4	9.7
16.5	275/570R13 (13354 A11)	CALL	Call		10.5-12.0	11.00	20	22.70	12.4	10.8
16.6	290/570R13 (13534 A-11)	448	Call		10.5-12.0	11.75	20	22.80	12.5	11.1
16.6	290/570R13 (15714 007)	448	Call		10.5-12.0	11.75	20	22.80	12.5	11.1
18.4	300/600R13 (11693 A11)	478	Call		13.0-14.0	13.00	20	23.90	14.7	11.9
18.4	300/600R13 (15506 007)	478	Call		13.0-14.0	13.00	20	23.90	14.7	11.9
18.4	300/600R13 (16070 222)	478	Call		13.0-14.0	13.00	20	23.90	14.7	11.9
18.4	300/600R13 (16989 333)	478	Call		13.0-14.0	13.00	20	23.90	14.7	11.9
22.0	330/620R13 (9482 A11)	557	Call		14.0 - 16.0	15.00	20	24.45	15.9	13.5
22.0	330/620R13 (15340 A545)	557	Call		14.0 - 16.0	15.00	20	24.45	15.9	13.5
NEW	230/550R15 (16432- 222)	0	Call		9.0-11.0	10.00	20	21.80	11.4	9.2
NEW	300/600R15 (16433- 222)	0	Call		13.0-14.0	13.00	20	23.90	14.7	11.9

Avon Radial "007" & "222" Compounds

Prices Subject To Change Without Notice

These compounds has many track records and is very consistent for long runs.

The harder you drive with this compound the better the tire works.

Note: In many sizes only the spec # shown is at that price. The price may be higher for alternate numbers or compounds!

Prices Subject to change without notice



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

**Autocross Compound A-11, A-24 & A-53
Avon Bias Ply Slicks**

	Slick	Historic New	Historic Old	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.	
	8.5/16.0-10 (7340-A11)	339		8.0 TO 9.5	9.00	20.0	15.9	9.3	8.0	
9.3	7.0/20.0-13 (10992 A-11)	248		6.0-8.0	6.00	20	20.80	7.6	7.4	
12	7.0/21.0-13 (11452 A-11)	259		6.0 TO 8.0	8.00	20	20.60	9.0	7.2	
	8.2/20.0-13 (2260-A11)	265		7.0 TO 9.0	9.00	20	19.95	9.8	8.5	
14	9.0/20.0-13 (7210-A11)	282		8.0 TO 10.5	10.00	20	20.00	10.6	9.2	
13	10.0/20.0-13 (2545-A11)	300		9.0 TO 11.0	10.00	20	19.80	11.1	10.2	
New	10.0/20.0-13 (14763 -A11) Kevlar	300		9.0 TO 11.0	10.00	20	19.80	11.1	10.2	
	10.0/21.0-13 (16577 -A11) F-1	335		9.0 TO 11.0	10.00	20	21.00	11.1	10.2	
15	8.2/22.0-13 (3146-A11)	298		7.0 TO 10.0	9.00	20	22.00	10.1	8.6	
14	9.2/22.0-13 (11453 A-11)	310		8.5-10.5	10.00	20	22.40	11.1	9.1	
15	10.0/22.0-13 (10358-A11)	328		9.0 TO 12.0	11.00	20	22.10	11.9	10.3	
15	9.0/21.0-13 (6428-A11)	299		8.0 TO 10.5	10.00	20	21.00	10.9	9.1	
19	10.5/23.0-13 (2126-A11)	375		9.0 TO 11.5	11.00	20	23.50	12.3	10.3	
19	10.5/23.0-13 (4125-A11) Rear	375		9.0 TO 11.5	11.00	20	23.50	12.3	10.3	
19	12.0/23.0-13 (7239A11)	375		12.0 TO 14.0	13.00	20	23.20	14.5	12.3	
20	13.0/23.0-13 (7262-A11)	392		13.0 TO 15.0	14.00	20	23.25	15.2	13.0	
21	13.0/24.5-13 (6429-A11)	407		13.0 TO 15.0	14.00	20	24.30	15.5	12.5	
27	15.0/26.0-13 (2133-A11)	499		15.0 TO 18.0	16.00	20	25.75	17.8	15.0	
28	16.2/26.0-13 (3354-A11)	533		16.0 TO 18.0	17.00	20	25.80	18.8	16.3	
			Historic New	Historic Old						
	8.0/21.5-15 (14765-A-11)(6881-A24)(12389-A56)	342	407	417	6.5 TO 8.5	7.50	30.0	21.8	8.8	7.8
	8.7/21.5-15 (14754 A11) (6460 A24) (48715 A15)	374	439	449	7.5 TO 9.5	8.00	30	22.10	9.7	8.4
	9.5/21.5-15 (4700-A24)	350	425	435	8.0-10.0	10.00	30	21.85	10.7	9.5
	9.5/21.5-15 (2829-A11) (3640 A15)	395	470	480	8.0-10.0	10.00	30	21.85	10.7	9.5
	10.7/21.5-15 (2036 A-11) (2412 A15)	365	440	450	9.0-11.0	10.00	30	21.85	11.3	10.6
	10.7/21.5-15 (12417) A-53 Kevlar	398	473	483	9.0-11.0	10.00	30	21.85	11.3	10.6
18	7.5/23.0-15 (5983-A24)	340	405	415	7.0 TO 8.5	8.00	30	22.80	8.5	7.4
19	8.5/23.5-15 (6524-A24)	385	450	460	7.0 TO 9.5	8.50	30	23.60	9.6	8.3
20	9.1/23.5-15 (6132-A11)(5978 A24)	399	464	474	8.0 TO 9.5	8.50	30	23.55	9.9	9.1
18	10.5/23.0-15 (3101-A11)	413	488	498	9.0 TO 12.0	11.00	30	23.55	12.0	10.3
18	10.5/23.0-15 (4301 A24)	446	521	531	9.0 TO 12.0	11.00	30	23.55	12.0	10.3
21	11.0/23.5-15 (3100-A11)	413	488	498	10.0 TO 12.0	11.00	30	23.30	12.1	11.3
21	11.0/23.5-15 (4263-A24)	455	530	540	10.0 TO 12.0	11.00	30	23.30	12.1	11.3
21	12.5/23.5-15 (2351 A-11)	463	548	558	11.0 TO 13.5	12.00	30	23.30	13.3	12.7
21	9.5/25.0-15 (9928-A24) (14426S-A11)	413	488	498	9.0 TO 11.0	10.00	30	24.80	11.7	9.3
22	11.0/25.0-15 (4284-A24) (14427-A11)	442	517	527	10.0 TO 12.0	12.00	30	24.70	13.6	11.3
24	13.0/25.0-15 (4319-A11)	460	545	555	11.5 TO 14.0	14.00	30	24.80	15.4	13.2
24	13.0/25.0-15 (3731A-24)	509	594	604	11.5 TO 14.0	14.00	30	24.80	15.4	13.2
27	15.0/26.0-15 (3127-A11)(4302A-24)	516	621	631	14.0 TO 17.0	16.00	30	25.80	17.4	15.0
27	16.2/26.0-15 (3831-A11)	549	654	664	16.0 TO 19.0	16.00	30	25.80	17.9	16.3
25	12.5/27.0-15 (4285-A24)(11764-A11)	465	550	560	11.5 TO 14.5	13.00	30	27.00	15.3	12.5
27	14.0/27.0-15 (3358-A11)(4300-A24)	470	575	585	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
28	16.0/27.0-15 (3099-A11)	531	636	646	15.0 TO 19.0	16.00	30	27.50	16.8	16.1
17	8.5/23.3-16 (6329-A24)	395	460	470	8.0 TO 9.5	8.00	30	23.50	9.6	8.8
19	10.0/23.5-16 (11760-A-11) (3742-A24)	413	488	498	10.0 TO 12.0	10.00	30	23.60	11.1	10.3
17.72	11.0/23.5-16 (3131 A-11)	430	505	515	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (4172 A-24)	445	520	530	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
17.72	11.0/23.5-16 (15111 A-37)	458	533	543	10.0 TO 12.0	11.00	30	23.60	12.6	11.3
22	11.0/25.0-16 (2992-A11)(5260 A37)	448	523	533	10.0 TO 12.0	12.00	30	24.75	13.3	11.3
23	12.5/25.0-16 (4247 A11)	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
22	12.5/25.0-16 (4147-A-24) 4PLY	499	584	594	11.5 TO 14.0	13.00	30	24.80	14.2	12.5
27	12.5/27.0-16 (15006 A-24)	484	569	579	11.5 TO 14.5	13.00	30	27.00	15.3	12.5
24	13.5/25.0-16 (11759) A-11	474	579	589	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
24	13.5/25.0-16 (3845) A-24	519	624	634	12.0 TO 14.5	14.00	30	25.00	15.2	13.4
26	13.2/27.0-16 (15013) A-24	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2
26	13.2/27.0-16 (15105) A-37	496	581	591	11.5 TO 14.5	12.00	30	27.00	15.1	13.2
26	14.0/27.0-16 (2993) A-11	471	576	586	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (15020) A-24	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0
26	14.0/27.0-16 (10774) A-37	529	634	644	13.0 TO 16.0	15.00	30	27.10	16.7	14.0

The A-24 compound is one range harder than A-11, Most but not all Wets are A-15.

Prices Subject To Change Without Notice

Prices Subject to change without notice



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2019

Avon's A-15 Compound is a very soft slick used for Hill Climbs, Auto Crossing or hand cut for wet use.

**Autocross Compound Tires A-15
Avon Bias Ply Slicks / Wets**

WT	Slick Tread	Slick Price	Wets Add 55 to 100 Per Tire	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
10"									
	7.0/16.0-10 (13758 A-15)	273		6.5 TO 8.0	7.50	20.0	15.9	7.8	7.0
	8.5/16.0-10 (10338 A15)	356		8.0 TO 9.5	9.00	20.0	15.9	9.3	8.0
13"									
	8.2/20.0-13 (2555 A-15)	265		7.0 TO 9.0	9.00	20	19.95	9.8	8.5
13.89	8.2/22.0-13 (14209 A-15)	376		7.0 TO 10.0	9.00	20	22.00	10.1	8.6
14.77	9.0/20.0-13 (2553) A-15	282		8.0 TO 10.5	10.00	20	20.00	10.6	9.2
15.45	9.0/21.0-13 (4619) A-15	356		8.0 TO 10.5	10.00	20	21.00	10.9	9.1
15.85	10.0/20.0-13 (4134) A-15	300		9.0 TO 11.0	10.00	20	19.80	11.1	10.2
16.95	10.0/22.0-13 (9772) A-15	406		9.0 TO 12.0	11.00	20	22.10	11.9	10.3
19.86	10.5/23.0-13 (2594) A-15 Rec Front	377		9.0 TO 11.5	11.00	20	23.50	12.3	10.3
18.63	10.5/23.0-13 (4864) A-15 Rec Rear	446		9.0 TO 11.5	11.00	20	23.50	12.3	10.3
21.05	12.0/23.0-13 (2888) A-15	430		12.0 TO 14.0	13.00	20	23.20	14.5	12.3
21.76	13.0/23.0-13 (2391) A-15	440		13.0 TO 15.0	14.00	20	23.25	15.2	13.0
26.44	15.0/26.0-13 (2595) A-15	499		15.0 TO 18.0	16.00	20	25.75	17.8	15.0
30.31	16.2/26.0-13 (5347) A-15	592		16.0 TO 18.0	17.00	20	25.80	18.8	16.3
15"									
	8.0/21.5-15 (4867) A-15 6 PL	367		6.5 TO 8.5	7.50	30.0	21.8	8.8	7.8
17.92	8.7/21.5-15 (4871) A-15	399		7.5 TO 9.5	8.00	30	22.10	9.7	8.4
15.82	9.5/21.5-15 (3640) A-15	414		8.0 TO 10.0	10.00	30	21.85	10.7	9.5
17.06	10.0/21.5-15 (3503) A-15	420		8.5 TO 11.0	10.00	30	21.85	10.0	11.0
18.4	10.7/21.5-15 (2412) A-15	368		9.0 TO 11.0	10.00	30	21.85	11.3	10.6
17.02	8.5/23.5-15 (9318) A-15	403		7.5 TO 9.5	8.50	30	23.60	9.6	8.5
16.24	9.1/23.5-15 (5602) A-15	411		8.0 TO 9.5	8.50	30	23.60	9.9	8.8
18.65	10.5/23.0-15 (3283) A-15	421		9.0 TO 12.0	11.00	30	23.55	12.0	10.3
21.62	11.0/23.5-15 (3284) A-15	423		10.0 TO 12.0	11.00	30	23.60	12.1	11.3
23.63	11.0/25.0-15 (2459) A-15	437		10.0 TO 12.0	12.00	30	24.70	13.6	11.3
23.05	13.0/25.0-15 (2424) A-15	539		11.5 TO 14.0	14.00	30	24.80	15.4	13.2
26.80	15.0/26.0-15 (3286) A-15	508		14.0 TO 17.0	16.00	30	25.80	17.4	15.0
26.16	12.5/27.0-15 (2253) A-15	533		13.0 TO 16.0	15.00	20	27.10	15.2	12.5
28.55	16.0/27.0-15 (3593) A-15	607		15.0 TO 19.0	16.00	30	27.50	16.8	16.1
16"									
	8.5/23.3-16 (9806) A-15	404		7.5 TO 8.0	8.00	30	23.55	9.6	8.8
16.24	9.5/23.5-16 (3647) A-15	426		8.5 TO 10.5	8.50	30	23.60	9.8	9.5
20.08	10.0/23.5-16 (3106) A-15	410		9.0 TO 11.0	10.00	30	23.60	11.1	10.0
18.56	11.0/23.5-16 (2458) A-15	458		10.0 TO 12.0	12.00	30	23.50	12.6	11.3
19.07	11.0/25.0-16 (2994) A-15	448		10.0 TO 12.0	12.00	30	24.75	13.3	11.3
23.63	12.5/23.5-16 (3604) A-15	496		11.5 TO 13.5	13.75	30	23.40	13.8	12.7
20.98	12.5/25.0-16 (12866) A-15	515		11.5 TO 13.5	13.00	30	24.75	14.2	12.5
25.96	13.5/25.0-16 (4116) A-15	471		12.0 TO 14.5	14.00	30	25.00	15.2	13.4
25.47	14.0/27.0-16 (2995) A-15	483		13.0 TO 16.0	14.00	30	27.20	15.8	14.0

**Avon Super Soft / Slick or Wet
Hill Climb - Autocross Compound Tires
Super Soft - Softer Than A-15**

There may be more sizes available, please call for availability.

Search A92, A45

Hill Climb, Auto Cross / Super Soft A92	Slick Price	Wets Price	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
7.2/20.0-13 (14254) A-92	293	Call	6.0 TO 8.0	8.0	20	20.2	9.0	7.1
8.2/20.0-13 (14140) A-92	312	Call	7.0 TO 9.0	9.0	20	19.95	9.75	8.5
9.0/20.0-13 (14143) A-92	322	Call	8.0 TO 10.0	10.0	20	20.0	10.65	9.2
10.0/20.0-13 (14251) A-92	340	Call	9.0 TO 11.0	10.0	20	19.8	11.1	10.2
7.0/21.0-13 (14207) A-92	307	Call	6.0 TO 8.0	8.0	20	20.6	9.0	7.2
8.5/21.5-13 (14176) A-92	351	Call	7.5 TO 9.0	9.0	20	20.8	10.2	8.5
9.0/21.0-13 (14177) A-92	351	Call	8.0 TO 10.0	10.0	20	21.0	10.9	9.1
9.2/22.0-13 (14142) A-92	375	Call	8.5 TO 10.5	10	20	22.4	11.1	9.1

Note: The A92 compound is the next to the softest tire Avon makes, the A45 is the softest compound made by Avon Racing.

Note: In many sizes only the spec # shown is at that price. The price may be higher for alternate numbers or compounds!

Prices Subject to change without notice