



Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone: 510-582-5031 Order Line 800-510-7223

Jan 2017

## Radical Tires From Avon Racing 2017

	Radical - SR3/SR8 Radials	Dry	Molded	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
		Slick	Wet						
16.1	205/580R15 (12347) A-53	338		7.0-8.0	7.00	20	22.83	8.6	8.2
17.3	265/600R16 (12348) A-53	374		10.0-12.0	10.75	20	23.60	11.4	10.3
16.1	205/580R15 (14660) A-514	338		7.0-8.0	7.00	20	22.83	8.6	8.2
17.3	265/600R16 (14706) A-514	374		10.0-12.0	10.75	20	23.60	11.4	10.3
16.1	205/580R15 (14245) A-94 H.C.	390		7.0-8.0	7.00	20	22.83	8.6	8.2
17.3	265/600R16 (14243) A-94 H.C.	494		10.0-12.0	10.75	20	23.60	11.4	10.3
	205/580R15 (14783) A-15 WET H.C.	354		7.0-8.0	7.00	20	22.83	8.6	8.2
	265/600R16 (14782) A-15 WET H.C.	390		10.0-12.0	10.75	20	23.60	11.4	10.3
	205/580R15 (13310) W- 532 WET		374	7.0-8.0	7.00	20	22.83	8.6	8.2
	265/600R16 (13772) W -532 WET		410	10.0-12.0	10.75	20	23.60	11.4	10.3
Radical 13" Radials		Slick	Wet	RIM SIZES	Rim Used	At Psi	DIA	SEC	T.W.
13.2	195/530R13 (12419 A-53)	311	Call	7.0-8.0	7.50	20	20.80	9.2	8.1
17.7	250/570R13 (14399 A-11)	332	Call	9.0-11.0	10.00	20	22.60	11.4	9.7

Dry Compounds - Soft A-53 / Medium Soft A-11 / Medium Hard A-514

Wet Compounds- Soft A-15 / Medium W-532

Hillclimb Compound A-94

Prices Subject To Change Without Notice