

Roger Kraus Racing

2896 Grove Way Castro Valley, Calif 94546. Phone 1-510-582-5031 Fax 1-510-886-5605



Radial Slicks & Wets for 2018

Jan-18

Formula F. Radials	RACER NET	RACING APPLICATION	TREAD WIDTH	TIRE DIAM	APPROX CIRC	RECOM RIM	MEASURED RIM	SECTION WIDTH	COMPOUND
185/60R13 R60A	212	Formula F.	6.4	21.8	68.2	5.5-6.0	6.0	7.7	R60A
205/60R13 R60A	212	Formula F.	8	22.7	71.7	5.5-6.0	6.0	8.7	R60A

Radial Slicks

01/2017

Hoosier Road Race Radial Slicks	RACER NET	RACING APPLICATION	TREAD WIDTH	TIRE DIAM	APPROX CIRC	RECOM RIM	MEASURED RIM	SECTION WIDTH	Soft >>>Hard COMPOUNDS
190/530R13	254	Prod, GTL	7.3	20.8	65.3	6-7	6.0	7.8	R80
215/530R13	276	Prod, GTL	8.3	20.8	65.4	6-7	7.0	8.8	R75, R80
210/550R13		PRO MAZDA	8.0	21.8	68.5	8-10	10.0	10.5	R35B R55A
275/570R13		PRO MAZDA	8.7	22.5	70.7	10-12	12.0	12.56	R35B R55A
200/580R15	351	Radical	8	22.9	71.9	6.5-8.0	8.0	8.8	R35A R45B
265/605R16	384	Radical	9.7	23.9	75.1	9-10	10.0	10.9	R35A
215/580R15	323	EP,FP,HP>L	8.6	22.9	71.8	7-9	7.0	9.7	R80, R100 S80
245/580R15	334	EP,FP,HP>L	9.4	22.9	72.0	7-10	7.0	10.0	R80 S80 S100
23.0x9.5R15	428	FA	9.4	22.9	72.0	10	10.0	10.7	FA, R25B R35A
23.5/13.0R15	425	FA							R25B
24.5/13.75R15	489	FA2	13.8	24.5	77.0	14	14.0	15.0	FA, R25B R35A
27.5X11.5R15	345	HSC FRT	11.5	27.4	86.1	10	9.5	12.8	HSC Comp
27.5X11.5R15	345	HSC REAR	11.5	27.4	86.1	10	9.5	12.8	HSC Comp
23.5X11.0R16	444	GT2	10.6	23.6	74.0	10	10.0	11.0	R75A
23.5X12.0R16	444	GT2	12.0	23.5	73.8	12	12.0	12.0	R75A R75
25.5X12.5R16 C2000	444	GT1	12.4	25.8	81.0	12.0	12.0	13.3	R75A
25.5X14.0R16 C2000	553	GT1	13.6	25.7	80.9	12	12.0	14.1	R75A
28.0X14.5R16 C2000	588	GT1	14.4	28.2	88.5	13.0	13.0	15.1	R75A
235/620R17	417		9.6	24.3	76.5	8-9.5	9.0	9.6	R100 S100
265/630R17	459		10.1	24.8	77.9	9-10-	10.0	10.7	S100
235/645R18	436		8.5	25.5	80.0	8-9.5	8.0	9.1	R80, R100
250/650R18	436		9.1	25.6	80.4	8.0-9.5	9.0	9.9	R100
240/640R18	459		9.1	25.5	80.4	8-9.5	9.0	9.8	S80, S100
255/645R18	478		9.8	25.5	80.0	10.0	10.0	10.9	S80, S100
265/645R18	478		10.1	25.5	80.6	9-11	10.0	10.9	S80, R100 S100
280/680R18	536		10.0	26.9	84.6	9.0-11.0	10.0	11.3	S100
285/645R18	516		10.9	25.5	80.0	10-12	11.0	11.7	R80, S100
305/645R18	536		11.8	25.6	80.6	11-13	12.0	12.7	S80, S100
305/680R18	560		12.0	26.7	84.0	13.0	13.0	13.5	S100
320/650R18	560		12.0	25.8	80.8	11-13	12.0	13.0	S100
310/710R18	560		12.3	28.2	88.4	10-12	12.0	13.6	S100
355/650R18	603		13.8	25.7	80.8	12-14	13.0	14.2	R80, S100
235/645R19	474		8.5	25.5	80.1	8-9.5	9.0	9.5	R100
295/680R19	536		9.8	26.9	84.5	10-12	11.0	11.7	R100

Radial Wets

Hoosier Road Race Radial Wets	RACER NET	RACING APPLICATION	TREAD WIDTH	TIRE DIAM	APPROX CIRC	RECOM RIM	MEASURED RIM	SECTION WIDTH	Wet COMPOUNDS
23.5X11.0R16	CALL	GT2	10.6	23.6	74.0	10	10	11.0	WET
25.5/12.5R16 C2000	447.00	GT1 SP	12.4	25.8	81.0	12.0	12	13.3	44671 WET
27.0/13.0R16 C2000	456.00	GT1 SP	12.9	27.2	85.5	12	12	14.2	44681 WET
25.5/12.5R16 C2000	562.00	Trans Am	12.4	25.8	81.0	12.0	12	13.3	44670 WET
28.0/14.0R16 C2000	565.00	Trans Am	13.9	28.2	88.5	13.0	13	15.1	44690 WET

TREAD PATTERN IS HAND GROOVED ON RADIAL WETS

Soft → Firm
WET R25B R35A R45B R75 R80 R100