

# Roger Kraus Racing

Roger Kraus Racing Inc. 2896 Grove Way. Castro Valley, Calif 94546

Phone 510-582-5031 Order Line 800-510-7223

## Superlite and Sebring Wheels for Racing and Street.

### Superlite wheels - 8 Spoke 4 and 5 Lug.

Wheel Part #	Wheel Size	Back Spacing Range	Center Bore	Weight #	Load Rating	Racer Price
SPL137	13X7	4-5 95MM, 105MM, 115MM	63MM TO 73MM	13.06	1520 LBS	189.00
SPL146	14X6	4-5 100M, 105MM, 118MM	63MM TO 73MM	13.77	1520 LBS	199.00
SPL147	14X7	4-5 100MM, 112MM, 125MM	63MM TO 73MM	15.79	1520 LBS	209.00
SPL157	15X7	4-5 100MM, 112MM, 130MM	63MM TO 73MM	17.41	1875 LBS	219.00
SPL158	15X8	4-5 100MM, 112MM, 130MM	63MM TO 73MM	18.22	1875 LBS	239.00
SPL1510	15X10	TBA	63MM TO 73MM		TBA	
SPL178	17X8	4-5 100MM, 112MM, 130MM	63MM TO 73MM	22.27	2200 LBS	345.00
SPL1795	17X9.5	TBA	63MM TO 73MM		TBA	

### Sebring Wheels (Daisy Style) 5 Spoke 5 Lug

Wheel Part #	Wheel Size	Back Spacing Range	Center Bore	Weight	Load Rating	Racer Price
SEB157	15X7	5 -100MM, 112MM, 125MM	69.1 TO 73.1	TBA	1875 LBS	
SEB158	15X8	5- 100MM, 112MM, 125MM	69.1 TO 73.1	19.18 LBS	1875 LBS	255.00

### Metric to Inch Conversion Chart.

Millimeter	To>	Inches
63.0	To>	2.480
69.1	To>	2.720
73.0	To>	2.874
73.1	To>	2.878
95.0	To>	3.740
100.0	To>	3.937
105.0	To>	4.134
112.0	To>	4.409
115.0	To>	4.528
118.0	To>	4.646
125.0	To>	4.921
130.0	To>	5.118

All wheels are gravity cast out of A356.3 grade aluminum. The wheels go through an aging process of 60 hours, once aged they go to heat treatment and are treated to T6 specifications. Once machining and drilling is done, powder coating is next. Then our signature diamond finished edge is machined into the outside, then clear powder coated.

April 2016



# TRANS AM RACE ENGINEERING

TRANS AM RACE ENGINEERING WHEELS ARE SPECIALLY MANUFACTURED FOR BOTH RACE AND ROAD. ENGINEERED FOR PERFORMANCE, BUILT TO LAST.



## SUPERLITE

### 13 X 6

97mm / 3.81"  
101mm / 4.00"  
111mm / 4.37"

### 13 X 7

93mm / 3.66"  
110mm / 4.37"  
115mm / 4.52"

### 14 X 6

101mm / 4.00"  
107mm / 4.21"

### 14 X 7

101mm / 4.00"  
110mm / 4.37"

### 15 X 7

112mm / 4.40"  
125mm / 4.92"

### 15 X 8

100mm / 4.00"  
112mm / 4.40"  
125mm / 4.92"

### 15 X 10

112mm / 4.40"  
125mm / 4.40"  
130mm / 4.95"



## SEBRING

### 15 X 7

101mm / 4.00"  
112mm / 4.40"  
125mm / 4.92"

### 15 X 8

101mm / 4.00"  
112mm / 4.40"  
125mm / 4.92"

- \* HIGH QUALITY \* MANUFACTURED WITH STEEL INSERTS
- \* AUSTRALIAN DESIGNED AND ENGINEERED
- \* OLD SCHOOL LOOKS, NEW SCHOOL TECHNOLOGY
- \* FOR HIGH PERFORMANCE DRIVING



[www.TransAmRaceEngineering.com](http://www.TransAmRaceEngineering.com)

Find us on Facebook 