

# Roger Kraus Racing Ent

2896 Grove Way. Castro Valley, Calif 94546

Phone 510-582-5031 Order Line 800-510 RACE

## TOYO TIRES™

3/18/2015

### Proxes R888 Race Tires

Prices Subject to Change Without Notice

		UTQG			Tread		Tread	Overall	Overall		
13"		Racer	Tread	Product	Rim Range	Width	Depth	Diameter	Width	Max Pres.	Max Load
17#	185/60VR13 80V	168.00	100 AA A	168280	5.0-5.5-6.5	7.0	6/32"	21.6	7.4	51#	992
19#	205/60VR13 86V	168.00	100 AA A	168270	5.5-6.5-7.5	7.8	6/32"	22.6	8.2	51#	1168
18#	225/45R13 84V		100 AA A	168760	7.0-7.5-8.5	8.7	6/32"	20.8	8.8	51#	1102
<b>14"</b>											
20#	205/55VR14 85V		100 AA A	168060	5.5-6.5-7.5	8.0	6/32"	22.8	8.4	51#	1135
21#	225/50VR14 89V		100 AA A	168070	6.0-7.0-8.0	8.9	6/32"	22.8	9.3	51#	1279
<b>15"</b>											
20#	195/50R15 82V		100 AA A	160560	5.5-6.0-7.0	7.5	6/32"	22.6	7.8	51#	1047
20#	205/50ZR15 86W		100 AA A	168200	5.5-6.5-7.5	8.0	6/32"	23.0	8.5	51#	1168
22#	225/50ZR15 91W		100 AA A	160680	6.0-7.0-8.0	8.7	6/32"	23.7	9.1	51#	1356
24#	235/50ZR15 94W		100 AA A	162860	6.5-7.5-8.5	9.2	6/32"	24.2	9.6	51#	1477
20#	225/45ZR15 94W		100 AA A	169020	7.0-7.5-8.5	8.7	6/32"	22.8	8.9	51#	1201
<b>16"</b>											
24#	205/55ZR16 90W		100 AA A	168220	5.5-6.5-7.5	7.9	6/32"	24.7	8.4	51#	1323
20#	195/50ZR16 90W		100 AA A	168290	5.5-6.0-7.0	7.5	6/32"	23.5	7.9	51#	1102
24#	225/50ZR16 92W		100 AA A	168150	6.0-7.0-8.0	8.7	6/32"	24.7	9.3	51#	1389
27#	255/50ZR16 99W		100 AA A	168050	7.0-8.0-9.0	10.0	6/32"	25.9	10.6	51#	1709
21#	225/45ZR16 89W		100 AA A	168260	7.0-7.5-8.5	8.7	6/32"	23.8	9.0	51#	1279
24#	245/45R16 94W		100 AA A	168030	7.5-8.0-9.0	9.4	6/32"	24.4	9.8	51#	1477
<b>17"</b>											
22#	215/45ZR17 91W RD		100 AA A	168160	7.0-8.0	8.2	6/32"	24.6	8.5	50#	1356
24#	225/45ZR17 94W RD		100 AA A	168170	7.0-7.5-8.5	8.7	6/32"	25	9.1	50#	1477
24#	235/45ZR17 93W		100 AA A	168190	7.5-8.0-9.0	9.1	6/32"	25.3	9.5	51#	1433
19#	205/40ZR17 84W RD		100 AA A	168180	7.0-7.5-8.0	8.0	6/32"	23.5	8.3	50#	1102
24#	235/40ZR17 90W		100 AA A	156650	8.0-8.5-9.5	9.4	6/32"	24.6	9.6	51#	1323
25#	245/40ZR17 91W		100 AA A	168130	8.0-8.5-9.5	9.4	6/32"	24.7	9.8	51#	1356
26#	255/40ZR17 94W		100 AA A	168140	8.5-9.0-10.0	10.2	6/32"	25.1	10.4	50#	1477
29#	275/40ZR17 98W		100 AA A	168010	9.0-9.5-11.0	10.9	6/32"	25.7	11.0	51#	1653
30#	315/35ZR17 102W		100 AA A	168540	10.5-11.0-12.5	11.8	6/32"	25.6	12.6	51#	1874
<b>18"</b>											
23#	225/40ZR18 92Y RD		100 AA A	168210	7.5-8.0-9.0	8.7	6/32"	25.1	8.8	50#	1389
25#	235/40ZR18 91Y		100 AA A	168230	8.0-8.5-9.5	9.4	6/32"	25.5	9.6	51#	1356
26#	245/40ZR18 93Y		100 AA A	159490	8.0-8.5-9.5	9.8	6/32"	25.7	12.0	51#	1433
29#	275/40ZR18 99W		100 AA A	168110	9.0-9.5-11.0	10.9	6/32"	26.7	11.0	51#	1709
26#	255/35ZR18 94Y RD		100 AA A	160980	8.5-9.0-10.0	10.1	6/32"	25.1	11.8	50#	1477
27#	265/35ZR18 97Y RD		100 AA A	168240	9.0-9.5-10.5	10.6	6/32"	25.4	10.8	50#	1609
28#	275/35ZR18 99Y RD		100 AA A	162800	9.0-9.5-11.0	10.9	6/32"	25.7	11.0	50#	1709
33#	305/35ZR18		100 AA A	162810	10.0-11.0-12.0	12.1	6/32"	26.3	12.4	51#	1819
28#	285/30ZR18 97Y RD		100 AA A	168250	9.5-10.0-10.5	11.4	6/32"	24.8	11.3	50#	1609
29#	295/30ZR18 98Y RD		100 AA A	160960	10.0-10.5-11.0	11.8	6/32"	25.1	11.8	50#	1653
30#	315/30ZR18 98Y		100 AA A	162820	10.5-11.0-11.5	12.5	6/32"	25.5	12.5	51#	1653
32#	335/30ZR18 102Y		100 AA A	162830	11.5-12.0-12.5	13.4	6/32"	26.0	13.3	51#	1874
<b>19"</b>											
25#	235/35ZR19 87Y		100 AA A	162850	8.0-8.5-9.5	9.3	6/32"	25.7	9.5	51#	1201
26#	265/30ZR19 93Y RD		100 AA A	168300	9.0-9.5-10.0	10.1	6/32"	25.4	10.6	50#	1433
29#	295/30ZR19 100Y RD		100 AA A	162840	10.0-10.5-11.0	11.8	6/32"	26.0	11.7	50#	1764
31#	305/30ZR19 102Y RD		100 AA A	168000	10.0-11.0-11.5	12.3	6/32"	26.5	12.0	50#	1874
<b>20"</b>											
32#	285/35ZR20 100Y		100 AA A	162980	9.5-10.0-11.0	10.8	6/32"	27.7	11.5	51#	1764
33#	315/30ZR20 101Y		100 AA A	162990	10.5-11.0-11.5	11.7	6/32"	27.6	12.5	51#	1819

It is recommended to shave the tires to 3/32" to 4/32" for serious competition use.

Shaving to less than 3/32" will increase performance but reduce tire life.

Hot pressures in competition will run from a minimum of 36# hot to a max of 46# hot, 40# hot is a good starting point. Running 2# to 4# higher pressures in the front tires will reduce understeer in most cases.

Remember that the tires will build up pressure in competition. Usual pressure build up is from 4# to 11#, this must be taken in account when setting cold pressures. If you are not sure of your hot pressures start with 7# lower than the desired hot pressures until you get a base line. The general rule is that more experienced and faster drivers will get the most tire pressure build up.

**Proxes RA-1 Race Tires**

WT	13"	Racer	UTQG			Rim Range	Tread Width	Tread Depth	Diameter		Max Pres.	Max Load
			Tread	Product					Overall	Cross		
18#	185/60VR13 80V	NA	100 AA A	236680	5.0-5.5- 6.5	6.3	8/32"	21.70	7.50	44#	992.00	
20#	205/60VR13 86V		100 AA A	236700	5.5-6.0-7.5	6.9	8/32"	22.60	8.20	44#	1158.00	
	15"											
20#	205/50ZR15	180.00	100 AA A	236840	5.5.6.0-7.5	7.8	8/32"	23.00	8.30	44#	1135.00	
	Shaved	205.00										
23#	225/45ZR15		100 AA A	236970	7.0-7.5-8.5	8.5	8/32"	22.90	9.00	44#	1201.00	
23#	225/50ZR15		100 AA A	236830	6.0-7.0-8.0	8.5	8/32"	23.70	9.10	44#	1323.00	
	16"											
23#	225/50ZR16		100 AA A	236890	6.0-7.0-8.0	8.5	8/32"	24.70	9.00	44#	1390.00	
27#	P255/50ZR16		100 AA A	236880	6.5-8.0-10.0	9.8	8/32"	25.80	10.30	44#	1687.00	
25#	245/45ZR16		100 AA A	236800	7.5-8.0-9.0	9.4	8/32"	24.40	9.80	44#	1477.00	
	17"											
24#	235/40R17 90W		100 AA A	236760	8.0-8.5-9.5	8.9	8/32"	24.00	10.00	44#	1323.00	
26#	255/40R17 94W		100 AA A	236770	8.5-9.0-10.0	9.8	8/32"	25.00	10.00	44#	1477.00	
29#	275/40ZR17		100 AA A	236780	9.0-9.5-11.0	10.4	8/32"	25.67	10.90	44#	1653.00	
	18"											
30#	275/35ZR18		100 AA A	236710	9.0-9.5-11.0	10.5	8/32"	25.55	10.94	44#	1521.00	

**Proxes RR - Race Tires**

Size	Racer	UTQG			Rim Range	Tread Width	Tread Depth	Diameter		Max Pres.	Max Load
		Tread	Product					Overall	Cross		
19.6#	205/50ZR15	185.00	40 C A	255000	5.5.6.5-7.5		4/32"	23.00	8.50	51#	1168.00
21.6#	225/50ZR15		40 C A	255080	6.0-7.0-8.0		4/32"	23.90	9.20	51#	1356.00
26#	P275/35ZR18 87-LL		40 C A	255070	9.0-9.5-11.0		4/32"	25.60	10.90	44#	1201.00

**Tire Shaving Prices:**

Does not include mounting and balancing charges.

RD= Reinforced

13" TO 15" = 25.00

16" = 30.00

17" = 30.00

18" = 35.00

19" = 40.00

**Prices subject to change without notice!**

It is recommended to shave the tires to 3/32" to 4/32" for serious competition use.

Shaving to less than 3/32" will increase performance but reduce tire life.

Hot pressures in competition will run from a minimum of 36# hot to a max of 46# hot, 40# hot is a good

starting point. Running 2# to 4# higher pressures in the front tires will reduce understeer in most cases.

Remember that the tires will build up pressure in competition. Usual pressure build up is from 4# to 11#,

this must be taken in account when setting cold pressures. If you are not sure of your hot pressures

start with 7# lower than the desired hot pressures until you get a base line. The general rule is that more experienced and faster drivers will get the most tire pressure build up.

**Toyo RR Toyo R888 Toyo RA1**