



Roger Kraus Racing

Operated by Modern Vintage Racing LLC
ph 1-510-582-5031 - 1-800-510-7223

Avon Radial Ply

W.T. Formula One Radial Ply

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
18	245/640R13 (13247 A11)	11-12.5	11.75	20	25.20	12.6	9.50
	<u>245/640R13 (13248 A-15)</u>	11-12.5	11.75	20	25.20	12.6	9.50
20	270/660R13 (12242 A11)	11-12.5	11.75	20	25.75	13.4	11.1
21	315/660R13 (11505 A11)	13-15	13.75	20	25.75	15.0	12.3
23	370/660R13 (9845 A11)	14-16	15.0	20	25.75	17.0	15.0
	<u>370/660R13 (9848 A-15)</u>	14-16	15.0	20	25.75	17.0	15.0

Avon Radial Ply

W.T. F3000 Radial Ply

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
17	245/600R13 (13919 A11) 10952W)	11-13	12.0	20	23.80	12.4	9.5
22	330/620R13 (9482 A11) (6021W)	14-16	15.0	20	24.45	15.9	13.5

Avon Radial Ply

W.T. INDY Car Radials

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
18	275/635R15 (13797 A11) NLM	11-13	10.0	20	25.30	11.9	10.7
22	350/72015 (12700 A11) NLM	14-16	14.0	20	28.31	16.3	13.9

Avon Radial Ply

W.T. Formula Atlantic - INDY Lights

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
15	240/600R15 (14188 A53) (16146 A333)	10-12	10.0	20	23.70	11.0	9.4
21	330/60R15 (14189 A53) (16147 A333)	14-16	14.0	20	24.40	15.5	13.9

Avon Radial Ply

W.T. Group C, IMSA

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	300/650R17 (15586 A24)	11-12.5	12.0	20	25.70	13.0	12.0
	300/650R18 (15407S A24) (15128 A545)	11-12.5	12.0	20	25.70	13.0	12.0
	320/705R18 (A11, A24, A545)	13-14	13.0	29	27.80	13.9	12.6
	335/645R18 (14744S A11)	13-14	13.0	20	25.55	14.2	13.1
	335/645R18 (15724S A24)	13-14	13.0	20	25.55	14.2	13.1
	335/645R18 (15984 A545)	13-14	13.0	20	25.55	14.2	13.1
	365/720R18 (15360 A11) (17511 A24)	14.5-16	14.5	20	28.39	15.9	14.4
	365/720R18 (15610 A545)	14.5-16	14.5	20	28.39	15.9	14.4

Avon Bias Ply

W.T. Formula B. F2, Early Sports Racers

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
15	9.1/21.0-13 (6428 A11)	8.5-10.5	10.0	20	21.0	10.9	9.1
19	12.0/23.0-13 (7239 A11)	12-14	13.0	20	23.2	14.5	12.3

Avon Bias Ply

W.T. Formula Atlantic - 2 liter Sports Racers

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
9.3	9.0/20.0-13 (7210 A11)	8-10.5	10.0	20	20.0	10.6	9.2
20	13.0/23.0-13 7262 A11)	13-15	14.0	20	23.35	15.2	13.00

Avon Bias Ply

W.T. Sports Racers - Spec Applications

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
12	7.0/21.0-13 (11452 A11)	6-8	8.0	20	20.6	9.0	7.2
17	9.2/22.0-13 (11453 A11)	8.5-10.5	10.0	20	22.4	11.1	9.1
9.3	7.0/20.0-13 (10992 A11,15763-222, 15502-007)	6-8	6.0	20	20.4	7.6	7.4
11.3	8.2/22.0-13 (10993 A11, 15766-222, 16479-007)	8-10	8.0	20	22.0	9.7	8.6

Avon Bias Ply

W.T. Formula B - Historic & Monoposto

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
15	8.2/22.0-13 (3146 A11) NLM	7-10	9.0	20	22.0	10.1	8.6
19	10.5/23.0-13 (4125 A11) Rear	9-11.5	11.0	20	23.5	12.3	10.3
15	9.1/21.0-13 (6428 A11)	8.5-10.5	10.0	20	21.0	10.9	9.1
19	12.0/23.0-13 (7239 A11)	12-14	13.0	20	23.2	14.5	12.3
20	13.0/23.0-13 7262 A11) (15760 222)	13-15	14.0	20	23.35	15.2	13.00
20	13.0/24.5-13 (6429 A11)	13-15	14.0	20	24.3	15.5	12.5

Hard

Avon Compounds

Medium

Very Soft

Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063



Roger Kraus Racing

Operated by Modern Vintage Racing LLC
ph 1-510-582-5031 - 1-800-510-7223

Avon Bias Ply

W.T. Formula 1 & Other

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.5/16.0-10 (7340 A11) (10338 A15)	8-9.5	9.0	20	15.9	9.3	8.0
	8.2/20.0-13 (2260 A11)(2555W)	7-9	9.0	20	19.95	9.8	8.5
14	9.0/20.0-13 (7210 A11) (2553W)	8-10.5	10.0	20	20.0	10.6	9.2
13	10.0/20.0-13 (2545 A11) (4134W)	9-11	10.0	20	19.8	11.1	10.2
	10.0/20.0-13 (14763 A11 Kevlar)	9-11	10.0	20	19.8	11.1	10.2
15	9.0/21.0-13 (4619 A15)	8-10.5	10.0	20	21.0	10.9	9.1
15	9.0/21.0-13 (6428 A11)	8-10.5	10.0	20	21.0	10.9	9.1
	10.0/21.0-13 (16577 A11) F1	9-11	10.0	20	21.0	11.1	10.2
15	10.0/22.0-13 (9772 A15)	9-12	11.0	20	22.1	11.9	10.3
15	10.0/22.0-13 (10358 A11)	9-12	11.0	20	22.1	12.1	10.3
19	10.5/23.0-13 (2126 A11 Frt) (4125 A11 Rear)	9-11.5	11.0	20	23.5	12.3	10.3
	10.5/23.0-13 (2594 A15 F1 Front)	9-11.5	11.0	20	23.5	12.3	10.3
18	10.5/23.0-15 (3101 A11)	9-12	11.0	30	23.55	12.0	10.3
21	13.0/24.5-13 (6429 A11)	13-15	14.0	20	24.3	15.5	12.5
27	15.0/26.0-13 (2133 A11) (2595 A15)	15-18	16.0	20	25.75	17.8	15.0
28	16.2/26.0-13 (3354 A11) (5347W)	16-18	17.0	20	25.8	18.8	16.3

Avon Bias Ply

W.T. FIA - Can Am - USRRC - Other

		Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
	8.0/21.5-15 (14765 A11) (12389 A56)	6.5-8.5	7.5	30	21.80	8.8	7.8
	8.0/21.5-15 (6881 A24)	6.5-8.5	7.5	30	21.80	8.8	7.8
	8.7/21.5-15 (14754 A11) (6460 A24) (4871 A15)	7.5-9.5	8.0	30	22.10	9.7	8.4
	9.5/21.5-15 (4700 A24)	10.0	10.0	30	21.85	10.7	9.5
	9.5/21.5-15 (2829 A11) (3640 A15) NLM	8-10	10.0	30	21.85	10.7	9.5
	10.7/21.5-15 (2036 A11) (2412 A15)	9-11	10.0	30	21.85	11.3	10.6
18	7.5/23.0-15 (5893 A24) NLM	7-8.5	8.0	30	22.85	8.5	7.4
19	8.5/23.5-15 (6524 A24) NLM	7-9.5	8.5	30	23.60	9.6	8.3
20	9.1/23.5-15 (6132 A11) (5978 A24)	8-9.5	8.5	30	23.55	9.9	9.1
18	10.5/23.0-15 (3101 A11)	9-12	11.0	30	23.55	12.0	10.3
18	10.5/23.0-15 4301 A24)	9-12	11.0	30	23.55	12.0	10.3
21	11.0/23.5-15 (3100 A11)	10-12	11.0	30	23.3	12.1	11.3
21	11.0/23.5-15 (4263 A24)	10-12	11.0	30	23.3	12.1	11.3
21	12.5/23.5-15 (2351 A11) (3733 A24)	11-13.5	12.0	30	23.3	13.3	12.7
21	9.5/25.0-15 (9928 A24) (14426 A11)	9-11	10.0	30	24.8	11.7	9.3
22	11.0/25.0-15 (4284 A24 NLM) (14427 A11)	10-12	12.0	30	24.7	13.6	11.3
24	13.0/25.0-15 (4319 A11)	11.5-14	14.0	30	24.8	15.4	13.2
24	13.0/25.0-15 (3731 A24)	11.5-14	14.0	30	24.8	15.4	13.2
27	15.0/26.0-15 (3127 A11) (4302 A24)	14-17	16.0	30	25.8	17.4	15.0
27	16.2/26.0-15 (3831 A11)	16-19	16.0	30	25.8	17.9	16.3
25	12.5/27.0-15 (4285 A24) (11764 A11)	11.5-14.5	13.0	30	27.0	15.3	12.5
27	14.0/27.0-15 (3358 A11) NLM	13-16	15.0	30	27.1	16.7	14.0
28	16.0/27.0-15 (3099 A11) NLM	15-19	16.0	30	27.5	16.8	16.1
17	9.5/23.5-16 (3533 A24)	8.5-10.5	8.5	30	23.6	9.8	9.5
19	10.0/23.0-16 (11760 A11 NLM) (3742 A24)	10-12	10.0	30	23.6	11.1	10.3
18	11.0/23.5-16 (3131 A11)	10-12	11.0	30	23.6	12.6	11.3
18	11.0/23.5-16 (4172 A24)	10-12	11.0	30	23.6	12.6	11.3
18	11.0/23.5-16 (15111 A37)	10-12	11.0	30	23.6	12.6	11.3
22	11.0/25.0-16 (2992 A11)	10-12	12.0	30	24.8	13.3	11.3
22	12.5/23.5-16 (3069 A11) (3081 A24 (3604 A15)	11-13.5	12.0	30	23.4	13.6	12.7
23	12.5/25.0-16 (4247 A11)	11.5-14	13.0	30	24.8	14.2	12.5
23	12.5/25.0-16 (4147 A24)	11.5-14	13.0	30	24.8	14.2	12.5
24	13.5/25.0-16 (11759 A11)	12-14.5	14.0	30	25.0	15.2	13.4
24	13.5/25.0-16 (3845 A24)	12-14.5	14.0	30	25.0	15.2	13.4
26	14.0/27.0-16 (2993 A11)	13-16	15.0	30	27.1	16.7	14.0
26	14.0/27.0-16 (15020 A24)	13-16	15.0	30	27.1	16.7	14.0

Hard

Avon Compounds

Medium

Very Soft

Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063



Roger Kraus Racing
Operated by Modern Vintage Racing LLC
 ph 1-510-582-5031 - 1-800-510-7223

Avon Radial Ply - Sports Racers

Wolf GB08 F Mistral / Extreme

250/570R13 (17742 222)

315/660R13 (17856 222)

Avon Bias Ply - SCCA

Formula Continental, S2 & F1000/FB Tires

9.3 7.0/20.0-13 (15502 007 **NLM**) (15763 222) (10992 A11)

11.3 8.2/22.0-13 (16479 007) (15766 222) (10993 A11)

15.0 9.2/22.0-13 (17810 007)

Formula Continental, S2 & F1000/FB WETS

12.85 160/530R13 (13593 W561)

15.45 180/565R13 (13594 W561)

SCCA Stohr, P1, P2, S.V. and F.M.

9.5 8.2/20.0-13 (17778 222) Light Wt For 2022

14.9 10.0/22.0-13 (17779 222) Light Wt For 2022

17 9.2/22.0-13 (17810 007) NEW

F.A & 2 liter Sports Racers

14.17 9.0/20.0-13 (17613 222 LW)

20.81 13.0/23.0-13 (15760 222)

SCCA GT3, E Production

17.5 9.0/23.3-15 (16972 A545)

Rim	Rim	AT				
Sizes	Used	PSI	Diam	Sec	T.W.	
9-11	10.0	20	22.6	11.4	9.7	
13-15	13.8	20	25.8	15.0	12.3	
Rim	Rim	AT				
Sizes	Used	PSI	Diam	Sec	T.W.	
6-8	6.0	20	20.8	7.6	7.4	
8-10	8.0	20	22.0	9.7	8.6	
8.5-10.5	10.0	20	22.4	11.1	9.1	
Sizes	Used	PSI	Diam	Sec	T.W.	
5.5-7.5	6.0	20	20.9	7.4	6.3	
5.5-8.5	7.0	20	22.1	8.7	7.2	
Sizes	Used	PSI	Diam	Sec	T.W.	
7-9	9.0	20	19.95	9.8	8.5	
9-12	11.0	20	22.1	11.9	10.3	
8.5-10.5	10.0	20	22.4	11.1	9.1	
Sizes	Used	PSI	Diam	Sec	T.W.	
8-10	9.0	20	20.0	10.6	9.2	
13-15	14.0	20	23.25	15.2	13.0	
Sizes	Used	PSI	Diam	Sec	T.W.	
7.0-9.5	7.0	30	23.47	9.5	9.0	

Avon Radial Ply - Sports Racers

Norma, Wolf, DP02. Indy Lights

Formula Atlantic 15" Radials

17.2 240/600R15 (14188 A53)**NLM**

22.68 330/620R15 (14189 A53)**NLM**

Special Application Radials

175/530R13 Spec Order

180/550R13 (15615 007)

180/550R13 (15259M W534 WET)

195/530R13 Special Order

210/550R13 (15485 007)

210/550R13 (17741 222 NEW 2021)

210/550R13 WET (16540MA) CR71

230/550R13 (15505 007) (16069 222)

250/570R13 (15616 007)

250/570R13 (17742 222 NEW 2021)

250/570R13 (15261 W534)

290/570R13 (15714 007)

290/570R13 (17743 222 NEW 2021)NLM****

290/570R13 WET (16539MA) CR71

300/600R13 (15506 007)

300/600R13 (16070 222) (16989 333)

300/600R13 (16943M W534)

315/660R13 (17856 222)

Rim	Rim	AT				
Sizes	Used	PSI	Diam	Sec	T.W.	
10-12	10.0	20	23.7	11.0	9.4	
14-16	14.0	20	24.4	15.5	13.3	
Sizes	Used	PSI	Diam	Sec	T.W.	
6.5-7.5	7.0	20	20.9	8.0	7.1	
8.5-9.5	9.0	20	21.8	9.5	7.3	
8.5-9.5	9.0	20	21.8	9.5	7.3	
8-9	8.5	20	20.8	9.7	8.1	
9-10	10.0	20	21.8	10.6	8.3	
9-10	10.0	20	21.8	10.6	8.3	
9-10	10.0	20	21.8	10.6	8.3	
9-11	10.0	20	21.8	11.4	9.2	
9-11	10.0	20	22.6	11.4	9.7	
9-11	10.0	20	22.6	11.4	9.7	
9-11	10.0	20	22.6	11.4	9.7	
10.5-12.5	11.75	20	22.8	12.5	11.1	
10.5-12.5	11.75	20	22.8	12.5	11.1	
10.5-12.5	11.75	20	22.8	12.5	11.1	
13-14	13.0	20	23.9	14.7	11.9	
13-14	13.0	20	23.9	14.7	11.9	
13-14	13.0	20	23.9	14.7	11.9	
13-15	13.8	20	25.8	15.0	12.3	
Sizes	Used	PSI	Diam	Sec	T.W.	
10-12	10.0	20	23.70	11.0	9.4	
14-16	14.0	20	24.40	15.5	13.3	

Formula Atlantic - INDY Lights

240/600R15 (14188 A53) (16146 A333)

330/620R15 (14189 A53) (16147 A333)

Hard

Avon Compounds

Medium

Very Soft

Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063



Roger Kraus Racing
Operated by Modern Vintage Racing LLC
 ph 1-510-582-5031 - 1-800-510-7223

Road Race - Avon Bias Ply Medium Soft

Autocrossing Compounds - Not Super Soft

	Rim Sizes	Wheel Used	PSI	Diam	Sec	T.W.
8.5/16.0-10 (7340 A11)	8-9.5	9.0	20	15.9	9.3	8.0
7.0/20.0-13 (10992 A11)	6-8	6.0	20	20.8	7.6	7.4
7.0/21.0-13 (11452 A11)	6-8	8.0	20	20.6	9	7.2
8.2/20.0-13 (2260 A11)	7-9	9.0	20	19.95	9.8	8.5
9.0/20.0-13 (7210 A11)	8-10.5	10	20	20.0	10.6	9.2
10.0/20.0-13 (2545 A11)	9-11	10	20	19.8	11.1	10.2
10.0/20.0-13 (14763 A11) Kevlar	9-11	10	20	19.8	11.1	10.2
9.0/21.0-13 (6428 A11)	8-10.5	10.0	20	10.9	9.1	9.1
10.0/21.0-13 (16577 A11) F1	9-11	10	20	21.0	11.1	10.2
8.2/22-13 (3146 A11)	7-9	9.0	20	22.0	10.1	8.6
8.2/22.0-13 (10993 A11)	8-10	8.0	20	22.0	9.7	8.6
9.2/22.0-13 (11453 A11)	8.5-10.5	10.0	20	22.4	11.1	9.1
10.0/22.0-13 (10358 A11)	9-12	11.0	20	22.1	11.9	10.3
10.5/23.0-13 (2126 A11) F1 Front	9-11.5	11.0	20	23.5	12.3	10.3
10.5/23.0-13 (4125 A111) Rear Use	9-11.5	11.0	20	23.5	12.3	10.3
12.0/23.0-13 (7239 A11)	12-14	13.0	20	23.2	14.5	12.3
13.0/23.0-13 (7262 A11)	13-15	14.0	20	23.25	15.2	13.0
13.0/24.5-13 (6429 A11)	13-15	14.0	20	24.3	15.5	12.5
15.0/26.0-15 (2133 A11)	15-18	16.0	20	25.8	17.8	15
16.2/26.0-13 (3354 A11)	16-18	17.0	20	25.8	18.8	16.3
8.0/21.5-15 (14765 A11) (6881 A24)	6.5-8.5	7.5	30	21.8	8.8	7.8
8.7/21.5-15 (14754 A11) (6460 A24)	7.5-9.5	8.0	30	22.1	9.7	8.4
9.5/21.5-15 (4700 A24)	8-10	10.0	30	21.85	10.7	9.5
9.5/21.5-15 (2829 A11) (3640 A15)	8-10	10.0	30	21.9	9.5	9.5
10.0/21.5-15 (14766 A11)	8.5-11	10.0	22	22.0	10.94	9.53
10.7/21.5-15 (2036 A11) (2412 A15)	9-11	10.0	30	21.85	11.3	10.6
7.5/23.5-15 (5983 A24)	7-8.5	8.0	30	22.8	8.5	7.4
8.5/23.5-15 (6524 A24)	7-9.5	8.5	30	23.6	9.6	8.3
9.1/23.5-15 (6132 A11) (5978 A24 S.O.)	8-9.5	8.5	30	23.55	9.9	9.1
10.5/23.0-15 (3101 A11)	9-12	11.0	30	23.55	12.0	10.3
10.5/23.0-15 (4301 A11)	9-12	11.0	30	23.55	12.0	10.3
11.0/23.5-15 (3100 A11)	10-12	11.0	30	23.3	12.1	11.3
11.0/23.5-15 (4263 A24)	10-12	11.0	30	23.3	12.1	11.3
12.5/23.5-15 (2351 A11)	11-13.5	10.0	30	23.3	13.3	12.7
9.5/25.0-15 (9928 A24) (14426 (A11)	9-11	10.0	30	24.8	11.7	9.3
11.0/25.0-15 (4284 A24) (14427 A11)	10-12	12.0	30	24.7	13.6	11.3
13.0/25.0-15 (4319 A11)	11.5-14	14.0	30	24.8	15.4	13.2
13.0/25.0-15 (3731 A24)	11.5-14	14.0	30	24.8	15.4	13.2
15.0/26.0-15 (3127 A11)	14-17	16.0	30	25.8	17.4	15
16.2/26.0-15 (3831 A11)	16-19	16.0	30	25.8	17.9	16.3
12.5/27.0-15 4285 A24) (11764 A11 NLM)	11.5-14.5	13.0	30	27.0	15.3	12.5
14.0/27.0-15 (3358 A11) (4300 A24)	13-16	15.0	30	27.1	16.7	14.0
16.0/27.0-15 (3099 A11)	15-19	16.0	30	27.5	16.8	16.1
10.0/23.5-16 (11760 A11) (3742 A24)	10-12	10.0	30	23.6	11.1	10.3
11.0/23.5-16 (3131 A11)	10-12	11.0	30	23.6	12.6	11.3
11.0/23.5-16 (4172 A24)	10-12	11.0	30	23.6	12.6	11.3
11.0/25.0-16 (2992 A11) (5260 A37)	10-12	11.0	30	24.8	12.6	11.3
12.5/25.0-16 (4247 A11) NLM	10-12	11.0	30	24.8	12.6	11.3
12.5/25.0-16 (4147 A24)	10-12	11.0	30	24.8	12.6	11.3
13.5/25.0-16 (11759 A11)	12-14.5	14.0	30	25.0	15.2	13.4
13.5/25.0-16 (3845 A24)	12-14.5	14.0	30	25.0	15.2	13.4
14.0/27.0-16 (2993 A11) NLM	13-16	15.0	30	27.1	16.7	14.0
14.0/27.0-16 15020 A24)	13-16	15.0	30	27.1	16.7	14.0

Hard

Avon Compounds

Medium

Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063



Avon Bias Ply Very Soft to Super Soft Tires

These Tires can be Hand Cut into wets

10-13"

7.0/16.0-10 (13758 A15)
8.5/16.0-10 (10338 A15)
8.2/20.0-13 (2555 A15)
8.2/22.0-13 (14209 A15)
9.0/20.0-13 (2553 A15)
9.0/21.0-13 (4619 A15)
10.0/20.0-13 (4134 A15)
10.0/22.0-13 (9772 A15)
10.5/23.0-13 (2594 A15 Rec Front)
10.5/23.0-13 (4864 A15 Rec Rear)
12.0/23.0-13 (2888 A15)
13.0/23.0-13 (2391 A15)
15.0/26.0-13 (2595 A15)
16.2/26.0-13 (5347 A15)

15"

8.0/21.5-15 (4867 A15 6 Ply)
8.7/21.5-15 (4871 A15)
9.5/21.5-15 (3640 A15)
10.0/21.5-15 (3503 A15)
10.7/21.5-15 (2412 A15)
8.5/23.5-15 (9318 A15)
9.1/23.5-15 (5602 A15)
10.5/23.0-15 (3283 A15)
11.0/23.5-15 (3284 A15)
11.0/25.0-15 (2459 A15)
13.0/25.0-15 (2424 A15)
15.0/26.0-15 (3286 A15)
12.5/27.0-15 (2253 A15)
16.0/27.0-15 (3593 A15)

16"

8.5/23.3-16 (9806 A15)
9.5/21.5-16 (3642 A15)
10.0/23.5-16 (3106 A15)
11.0/23.5-16 (2458 A15)
11.0/25.0-16 (2994 A15)
12.5/23.5-16 (3604 A15)
12.5/25.0-16 (12866 A15)
13.5/25.0-16 (4116 A15)
14.0/27.0-16 (2995 A15)

Super Soft Tires

Avon Bias Ply - Auto X, H.C & Wet

Auto X, H.C., A92 Comp. - Super Soft

7.2/20.0-13 (14254 A92) **NLM**
8.2/20.0-13 (14140 A92)
9.0/20.0-13 (14143 A92) NLM
10.0/20.0-13 (14251 A92)
7.0/21.0-13 (14207 A92)
8.5/21.5-13 (14176 A92)
9.0/21.0-13 (14177 A92)
9.2/22.0-13 (14142 A92)

Note: The A15 is a Hill Climb, Autocrossing and a Wet use tire. For wet use we hand grove these tires in house. These tires have more tread depth compared to other slicks.

Avon Bias Ply - Road Race, Auto X, H.C & Wet.

Autocrossing - Soft to Super soft Tires

Rim Sizes	Rim Used	AT PSI	Diam	Sec	T.W.
6.5-8	7.5	20	15.9	7.8	7.0
8-10.5	9	20	15.9	9.3	8.0
7-9	9	20	20.0	9.8	8.5
7-10	9	20	22.0	10.1	8.6
8-10.5	10	20	20.0	10.6	9.2
8-10.5	10	20	20.9	9.1	9.1
9-11	10	20	19.8	11.1	10.2
9-12	11	20	22.1	11.9	10.3
9-11.5	11	20	23.5	12.3	10.3
9-11.5	11	20	23.5	12.3	10.3
12-14	10	20	23.2	14.5	12.3
13-15	14	20	23.3	15.2	13.0
15-18	16	20	25.8	17.8	15.0
16-18	17	20	25.8	18.8	16.3
Sizes	Used	PSI	Diam	Sec	T.W.
6.5-8.5	7.5	30	21.8	8.8	7.8
7.5-9.5	8	30	22.1	9.7	8.4
8-10	10	30	21.9	10.7	9.5
8.5-11	10	30	21.9	11	10.0
9-11	10	30	21.9	11.3	10.6
7.5-9.5	8.5	30	23.6	9.6	8.5
8-9.5	8.5	30	23.6	9.9	8.8
10-12	11	30	23.55	12	10.3
11-12	11	30	23.0	12.1	11.3
10-12	12	30	24.7	13.6	11.3
11.5-14	14	30	24.8	15.4	13.2
14-17	16	30	25.8	17.4	15.0
13-16	15	30	27.1	15.2	12.5
15-19	16	30	27.5	16.8	16.1
Sizes	Used	PSI	Diam	Sec	T.W.
7.5-8	8	30	23.6	9.6	8.8
8-10	10	30	21.9	10.7	9.5
9-11	10	30	23.6	11.0	10
10-12	12	30	23.5	12.6	11.3
10-12	12	30	24.8	13.3	11.3
11.5-13.5	13.75	30	23.4	13.8	12.7
11.5-13.5	13	30	24.8	14.2	12.5
12-14.5	14	30	25	15.2	13.4
13-16	14	30	27.2	15.8	14

Hard

Avon Compounds

Medium

Very Soft

Super Soft

A29,A64,A84,A37,A745,A514,A24,A545,A11,007,222,333,A53,379,A50,A15,475,046,315,A94,A92,063